

CRWQ-72B

7,000 lumens, WQXGA, single-chip DLP projector



- **Razor-sharp images with vibrant colors**
- **Large lens shift range for flexible installation**
- **Compact design**
- **24/7 reliability**

*Only available at selected distributors

What's more, the CRWQ-72B replaces complex setups with multiple displays to get a high-resolution display in your meeting room, collaboration room or visualization room.

High-contrast images

The CRWQ-72B projector combines a unique WQXGA (2,560 x 1,600) resolution - much higher than any other single-chip DLP projector - with a light output of 7,000 lumens. The projector enables showing more data on screen simultaneously which has a documented effect on work efficiency, because more pixels equal more information that can be shown.* As it provides stable and high-contrast images that allow you to concentrate better and offers a low noise level, you can turn your meeting room into an efficient collaboration room.

Flexible installation

Next to having the smallest installation footprint, the CRWQ-72B is also the lightest projector in the 6,500 to 10,000 lumens segment. Thanks to its range of all-glass and high-quality lenses with wide lens shift, it offers ultimate installation flexibility.

Built to last

The CRWQ-72B features a filter-free design and reliable DLP® technology for unmatched picture accuracy and low total cost of ownership. Designed for unlimited use, it also comes with a three-year warranty, for true peace of mind.

Product specifications**CRWQ-72B****General specifications**

Projector type	single-chip DLP projector
Technology	LVDC DMD™ with DarkChip3™
Resolution	2,560 x 1,600 (WQXGA)
Brightness	7,000 ANSI lumens
Contrast ratio	6,500:1
Brightness uniformity	>90%
Aspect ratio	16:10
Lens type	All glass lenses
Lenses	wide angle lens EN42 (0.8:1), ultra wide zoom lens EN46 (0.8-1.21:1), wide angle lens EN43 (1.2-1.7:1), standard zoom EN41 (1.7-2.5:1), long throw zoom EN44 (2.50-4.60 :1), ultra wide fixed EN47 (0.65 : 1)
Optical lens shift	Vertical: -144% to +144%; Horizontal: -70% to +70% (on zoom lenses)
Color correction	RealColor™
Lamps	2 x 300W UHP Vidi
Lamp lifetime	Up to 2,000 hours (full power) / Up to 2,500 hours (eco mode)
Lamp house, quick replace	yes
Lamp warranty	500 hours or 90 days
Sealed DLP™ core	Yes
Orientation	table -ceiling
Inputs	2 x DVI-I; 2 x HDMI 1.3a; 2 x VGA; Video inputs; 1 x component; 1 x S-video
Input resolutions	Up to 2,560 x 1,600 pixels input on all models. Output resolution depends on native resolution; HDTV (1080p, 1080i, 720p); EDTV (576p, 480p); SDTV (576i, 480i); NTSC, PAL, SECAM; progressive scan
Software tools	Projector Toolset, ProNet
Control	1 x RJ-45 TCP/IP; 1 x 9-pin D-SUB RS232; 2 x 12V programmable trigger (3.5mm mini jack); 1 x Wired Remote 3.5mm mini jack; 2 x USB
Network connection	10/100 base-T, RJ-45 connection
Power requirements	100-240V / 50-60Hz
Power consumption	912W
Noise Level	34 dB
Operational ambient temperature	10-40°C / 50°-104°F
Operational humidity	20-80% RH
Dissipation BTU	max 3,109 BTU/h
Dimensions (WxLxH)	510 x 376 x 233 mm / 20.08 x 14.80 x 9.17 inches
Weight	12.7 kg (28.0 lbs)
Standard accessories	Power cord, wireless remote control
Certifications	Compliant with FCC, part 15 Class A and CCC, cCSAus, cUL, UL and CE
Warranty	Limited 3 years parts and labor. Extendable up to 5.

Last updated: 09 Jul 2024

© 2024 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.