

OpSpace OpS-210

Medium form factor thin client for WUXGA/WQHD/4K displays



Barco's OpS-210 thin client is a medium form factor display controller specifically built to drive up to two displays in WUXGA resolution (1920 x 1200), or two displays in WQHD resolution (2560 x 1440), or one display in UHD/4K resolution (3840 x 2160). It is used in Barco OpSpace networked visualization and collaboration environments to display encoded streams coming from an IP network. It supports standard H.264, Barco's low-latency Video2Data (V2D), Barco ProServer/Virtual Network Computing (VNC) and Remote Display Protocol (RDP) decoding.

The OpS- 210 runs a redundant network interface for secured operation.

High density thin client for up to two displays

The OpS-210 is designed and fully qualified for Barco OpSpace environments. Once connected to an OpSpace server, the pre-configured appliance enables customers to capture networked source information from anywhere. It displays these sources with a user-friendly user interface.

Multiple appliances can be combined to show sources as part of a composed desktop on monitors of an OpSpace workstation, a truly unified workspace for mission-critical applications.

This thin client can process up to twelve HD-quality sources and allows organizing visual and interactive content as a smart multi-viewer to enhance knowledge and decision-making.

Features:

- Pre-configured thin client for Barco OpSpace systems
- Linux based OpSpace operating system
- Intel ® i7 Quad Core TM processor for low-latency application processing and software based media decoding
- Drives up to two displays in WUXGA resolution (1920 x 1200), or two displays in WQHD resolution (2560 x 1440), or one display in UHD/4K resolution (3840 x 2160)
- Processes up to twelve HD sources
- Universal IP streaming video decoding (H.264, V2D, ProServer/VNC, RDP)
- Silent operation
- Medium form factor
- Redundant network interface

Product specificaties**OPSPACE OPS-210**

General specifications	
Besturingssysteem	Linux
Geheugen	8 GB
Harde schijf	128 GB Solid-State Disk SSD
Netwerk	2x 1Gb/s LAN
Grafische kaart	Professional high-performance NVIDIA Quadro-series graphic card
Processor	Intel(R) Core(TM) i7 Quad core 4GHz processor
Uitgang	Up to 2x displays WUXGA 1920x1200 @60Hz (Display Port 1.2/OPS) Up to 2x displays WQHD 2560x1440 @60Hz (Display Port 1.2/OPS) Up to 1x display UHD 3840x2160 @60Hz (Display Port 1.2/OPS)
Invoer	IP video sources (H.264), Video2Data (Barco V2D), Virtual Network Computing (VNC), Remote Desktop Protocol (RDP)
Vormgeving	3U ½ 19" Rackmount housing
Afmetingen	133mm x 220mm x 300mm 5.24in x 8.66in x 11.81in
Voeding	100-240V, 5-3A, 50/60Hz
Energieverbruik	Typ. 124W max. 270W
Temperatuurbereik	0° -40°C 32° -104°F
Vochtigheid	Max. 80% (noncondensing)
Geluidsniveau	Max. 36dba (measured at 1m/32.8ft distance at 22°/72)
Naleving	CE, CB, IEC 609501, ETC, FCC Class A, CCC, BIS, CU-EAC Regulatory model ID: NGP-210
Bestelgegevens	R9821004B OpS-210 ThinClient Large Model US R9821004F OpS-210 ThinClient Large Model EU R9821004G OpS-210 ThinClient Large Model UK R9821004I OpS-210 ThinClient Large Model CN R9821004X OpS-210 ThinClient Large Model C13/C14 R9821004 OpS-210 ThinClient Large Model No Power Cable

Laatst bijgewerkt: 15 Mar 2023

© 2018 Barco nv. Alle rechten voorbehouden. Gehele of gedeeltelijke reproductie zonder schriftelijke toestemming is verboden. Alle merknamen en productnamen zijn handelsmerken, geregistreerde handelsmerken of handelsnamen van hun respectieve houders. Vanwege voortdurende innovatie kunnen informatie en technische specificaties zonder voorafgaande kennisgeving worden gewijzigd. Raadpleeg www.barco.com voor de meest recente specificaties.