

# iD H250

1080p HD, 2,500 lumens single-chip DLP projector



## Especificações técnicas

## ID H250

### Especificações gerais

Saída de luz	2500 ANSI lumens
Resolução	HDTV (1920x1080)
Uniformidade de brilho	Greater than 95% for the entire screen
Razão de contraste	2,000:1 (full white/full black)
Visor	<ul style="list-style-type: none"><li>• 1-chip 0.95" native 1080x1920p HD resolution</li><li>• DarkChip3® DLP® panel with BrilliantColor processing</li></ul>
Recursos	<ul style="list-style-type: none"><li>• Automatic scaling of non-native resolutions</li><li>• Sealed optical engine and lightpipe</li><li>• Filterless design</li><li>• Remote control through RS232 and TCP/IP</li><li>• Standard cable basket included</li></ul>
Entradas	<ul style="list-style-type: none"><li>• 1x Component Video, RGBHV, RGBS or RGSB (5x BNC)</li><li>• 1x Composite Video (BNC)</li><li>• 1x S-Video (4-pin mini-DIN)</li><li>• 1x VGA (D15 connector)</li><li>• 2x DVI-D (Digital Visual Interface-Digital)</li></ul>
Saída	<ul style="list-style-type: none"><li>• 1x DVI-D</li></ul>
Compatibilidade	<ul style="list-style-type: none"><li>• PAL, SECAM, NTSC signals</li><li>• Composite or S-video</li><li>• Component or RGB formats.</li><li>• All current HDTV, extended and improved television standards</li><li>• Most sources with a pixel clock up to 270 MHz</li><li>• All computer graphics formats from VGA, S-VGA, XGA, S-XGA and U-XGA (75 Hz)</li><li>• Apple Macintosh formats</li><li>• Electronic workstations with a resolution up to 1600 x 1200 pixels/75 Hz</li><li>• DVI sources up to UXGA and HDTV</li></ul>
Frequências de Varredura	<ul style="list-style-type: none"><li>• Horizontal 15 kHz -140 kHz</li><li>• Vertical 25 Hz -150 Hz</li></ul>
Conexão de rede	<ul style="list-style-type: none"><li>• 1x D9 connectors for RS232</li><li>• 1x IR remote receiver</li><li>• 1x RJ45 (Ethernet)</li></ul>
Lâmpada	<ul style="list-style-type: none"><li>• 2 x 250 Watt P-VIP lamp, in lamp housing, pre-aligned for max. light output.</li><li>• Typical lifetime: 1,500 h/lamp.</li></ul>
Lentes	<p>High quality zoom lenses</p> <ul style="list-style-type: none"><li>• QCLD (1.1-1.3:1) / R9849850</li><li>• CLD (1.2-1.6:1) / R9849870</li><li>• CLD (1.6-2.4:1) / R9849880</li><li>• CLD (2.4-4.3:1) / R9849890</li></ul> <p>Fixed focal length lens</p> <ul style="list-style-type: none"><li>• QCLD (0.85:1) / R9849860</li></ul>
Deslocamento Vertical de Lente	Max. vertical shift from -25% to +140% (+/-25% for QCLD (0.85:1) lens)
Energia	<ul style="list-style-type: none"><li>• 730 Watt max power consumption</li><li>• Power factor pre-regulated SMPS</li><li>• 90-254 VAC / 50-60Hz</li></ul>
Dimensões	<ul style="list-style-type: none"><li>• Length 590mm / 23.23in</li><li>• Width 415mm / 16.34in</li><li>• Height 195mm / 7.68in</li></ul>
Regulamentos de Segurança	<ul style="list-style-type: none"><li>• Compliant with ETL60950 and EN60950</li><li>• Compliant with FCC rules &amp; regulations, part 15 CE EN55022 Class A and CCC</li></ul>

Gerada em: 09 Jul 2024

© 2024 Barco nv. Todos os direitos reservados. A reprodução total ou parcial sem permissão por escrito é proibida. Todos os nomes de marca e produto são marcas comerciais, marcas comerciais registradas ou nomes dos respectivos proprietários. Por causa da inovação contínua, as informações e as especificações técnicas estão sujeitas a alterações sem aviso prévio. Verifique [www.barco.com](http://www.barco.com) para obter as especificações mais recentes.