F21 series

Entry-level Full HD DLP projector



The F21 series is an entry-level yet powerful single-chip DLP projector that shares many of its benefits with the other heavy-duty family members of the F-series. The F21 has been designed for business users and corporations. With 1080p resolution, DLP® technology and unmatched compatibility, it works with virtually anything you connect it to. Thanks to its standard pearl white housing, the F21 blends perfectly into any office environment.

Great image quality

The F21 offers a standard full HD image $1,920 \times 1,080$ resolution to offer users high-performance imaging. Thanks to the F21's outstanding resolution, colors and picture accuracy, you will be able to present in ultimate image quality.

Standard RealColor color management

The unique RealColor color management suite ensures perfect color reproduction and ensures the company logo is depicted how it's supposed to. Product presentations and corporate profiles look as good as they do in real life and on printed paper.

Low operating noise level

In many meeting rooms, the noise of a projector can be disturbing but this is not the case for the F21. Its magnesium and ceramic chassis offers low noise. The chassis is also used for heat dissipation, and all moving parts are decoupled from the chassis to guarantee low noise.

Simple and secure asset management

Built-in networking allows remote asset management through an easy-to-use web interface, or through the dedicated ProNet 2.0 asset management software. It also enables easy integration into IP and RS232C-based control systems. Moreover, a 4-digit pin code password protection prevents unauthorised use.



| Product specifications | F21 SERIES |
|---|--|
| General specifications | |
| Concept | lens shift design |
| Color wheel | High Brightness |
| Resolution | 1080p (1,920 x 1,080) |
| Brightness | Up to 3,000 lumens (max) |
| Technology | single chip DLP technology |
| Contrast | Up to 2,500 : 1 (Full field on/off) |
| Aspect ratio | 16:9 (1080p) |
| Display colors | 30-bit RGB |
| Computer graphics formats | 1,920 x 1,080 -pixel resolution |
| Horizontal scan frequencies | 15 -150 kHz (resolution dependant) |
| Vertical scan frequencies | 48 -190 Hz (resolution dependant) |
| Video formats | HDTV (1080p, 1080i, 720p) EDTV (576p, 480p) SDTV (576i, 480i) NTSC, PAL, SECAM progressive scan |
| Lens operation | Focus, Shift and Manual zoom |
| Lenses | Standard projection lens |
| | F 2.6 / 503-0075-00 Focus range: 1.5 - 10.0 m Throw ratio 1.60 - 2.21 : 1 (1080p) |
| Image width | 0.7 -7 m |
| Light source | 220W UHP lamp |
| Light source | 220W OTH MANP |
| Lamp lifetime | Up to 2,250 hours (Full power) Up to 3,000 hours (Eco mode) |
| | |
| Lamp lifetime | Up to 2,250 hours (Full power) Up to 3,000 hours (Eco mode) |
| Lamp lifetime Computer inputs | Up to 2,250 hours (Full power) Up to 3,000 hours (Eco mode) 1 x DVI-D 1 x HDMI 1.3a 1 x VGA |
| Lamp lifetime Computer inputs Video Input | Up to 2,250 hours (Full power) Up to 3,000 hours (Eco mode) 1 x DVI-D 1 x HDMI 1.3a 1 x VGA 1 x HDMI 1.3a 1 x Component 1 x S-video 1 x Video |
| Lamp lifetime Computer inputs Video Input Control possibilities | Up to 2,250 hours (Full power) Up to 3,000 hours (Eco mode) 1 x DVI-D 1 x HDMI 1.3a 1 x VGA 1 x HDMI 1.3a 1 x Component 1 x S-video 1 x Video 1 x RJ-45 TCP/IP 1 x 9-pin D-SUB RS232 1 x USB |
| Lamp lifetime Computer inputs Video Input Control possibilities Dimensions | Up to 2,250 hours (Full power) Up to 3,000 hours (Eco mode) 1 x DVI-D 1 x HDMI 1.3a 1 x VGA 1 x HDMI 1.3a 1 x Component 1 x S-video 1 x Video 1 x RJ-45 TCP/IP 1 x 9-pin D-SUB RS232 1 x USB 278 x 94 x 234 mm (WxHxD) |
| Lamp lifetime Computer inputs Video Input Control possibilities Dimensions Weight | Up to 2,250 hours (Full power) Up to 3,000 hours (Eco mode) 1 x DVI-D 1 x HDMI 1.3a 1 x VGA 1 x HDMI 1.3a 1 x Component 1 x S-video 1 x Video 1 x RJ-45 TCP/IP 1 x 9-pin D-SUB RS232 1 x USB 278 x 94 x 234 mm (WxHxD) 2.7 kg |
| Lamp lifetime Computer inputs Video Input Control possibilities Dimensions Weight Shipping Dimensions | Up to 2,250 hours (Full power) Up to 3,000 hours (Eco mode) 1 x DVI-D 1 x HDMI 1.3a 1 x VGA 1 x HDMI 1.3a 1 x Component 1 x S-video 1 x Video 1 x RJ-45 TCP/IP 1 x 9-pin D-SUB RS232 1 x USB 278 x 94 x 234 mm (WxHxD) 2.7 kg 440 x 440 x 380 mm (WxHxD) |
| Lamp lifetime Computer inputs Video Input Control possibilities Dimensions Weight Shipping Dimensions Power requirements | Up to 2,250 hours (Full power) Up to 3,000 hours (Eco mode) 1 x DVI-D 1 x HDMI 1.3a 1 x VGA 1 x HDMI 1.3a 1 x Component 1 x S-video 1 x Video 1 x RJ-45 TCP/IP 1 x 9-pin D-SUB RS232 1 x USB 278 x 94 x 234 mm (WxHxD) 2.7 kg 440 x 440 x 380 mm (WxHxD) 3.0-1.3A, ~100-240V, 50-60Hz |
| Lamp lifetime Computer inputs Video Input Control possibilities Dimensions Weight Shipping Dimensions Power requirements Conformances | Up to 2,250 hours (Full power) Up to 3,000 hours (Eco mode) 1 x DVI-D 1 x HDMI 1.3a 1 x VGA 1 x HDMI 1.3a 1 x Component 1 x S-video 1 x Video 1 x RJ-45 TCP/IP 1 x 9-pin D-SUB RS232 1 x USB 278 x 94 x 234 mm (WxHxD) 2.7 kg 440 x 440 x 380 mm (WxHxD) 3.0-1.3A, ~100-240V, 50-60Hz cCSAus, FCC Class A, cUL, UL and CE |
| Lamp lifetime Computer inputs Video Input Control possibilities Dimensions Weight Shipping Dimensions Power requirements Conformances Operating temperature | Up to 2,250 hours (Full power) Up to 3,000 hours (Eco mode) 1 x DVI-D 1 x HDMI 1.3a 1 x VGA 1 x HDMI 1.3a 1 x Component 1 x S-video 1 x Video 1 x RJ-45 TCP/IP 1 x 9-pin D-SUB RS232 1 x USB 278 x 94 x 234 mm (WxHxD) 2.7 kg 440 x 440 x 380 mm (WxHxD) 3.0-1.3A, ~100-240V, 50-60Hz cCSAus, FCC Class A, cUL, UL and CE |
| Lamp lifetime Computer inputs Video Input Control possibilities Dimensions Weight Shipping Dimensions Power requirements Conformances Operating temperature Storage temperature | Up to 2,250 hours (Full power) Up to 3,000 hours (Eco mode) 1 x DVI-D 1 x HDMI 1.3a 1 x VGA 1 x HDMI 1.3a 1 x Component 1 x S-video 1 x Video 1 x RJ-45 TCP/IP 1 x 9-pin D-SUB RS232 1 x USB 278 x 94 x 234 mm (WxHxD) 2.7 kg 440 x 440 x 380 mm (WxHxD) 3.0-1.3A, ~100-240V, 50-60Hz cCSAus, FCC Class A, cUL, UL and CE 10 -40 °C -20 -60 °C |
| Lamp lifetime Computer inputs Video Input Control possibilities Dimensions Weight Shipping Dimensions Power requirements Conformances Operating temperature Storage temperature Operating humidity | Up to 2,250 hours (Full power) Up to 3,000 hours (Eco mode) 1 x DVI-D 1 x HDMI 1.3a 1 x VGA 1 x HDMI 1.3a 1 x Component 1 x S-video 1 x Video 1 x RJ-45 TCP/IP 1 x 9-pin D-SUB RS232 1 x USB 278 x 94 x 234 mm (WxHxD) 2.7 kg 440 x 440 x 380 mm (WxHxD) 3.0-1.3A, ~100-240V, 50-60Hz cCSAus, FCC Class A, cUL, UL and CE 10 -40 °C -20 -60 °C 20 -80% RH |
| Lamp lifetime Computer inputs Video Input Control possibilities Dimensions Weight Shipping Dimensions Power requirements Conformances Operating temperature Storage temperature Operating humidity Storage humidity | Up to 2,250 hours (Full power) Up to 3,000 hours (Eco mode) 1 x DVI-D 1 x HDMI 1.3a 1 x VGA 1 x HDMI 1.3a 1 x Component 1 x S-video 1 x Video 1 x RJ-45 TCP/IP 1 x 9-pin D-SUB RS232 1 x USB 278 x 94 x 234 mm (WxHxD) 2.7 kg 440 x 440 x 380 mm (WxHxD) 3.0-1.3A, ~100-240V, 50-60Hz cCSAus, FCC Class A, cUL, UL and CE 10 -40 °C -20 -60 °C 20 -80% RH 10 -90% RH 3 years standard warranty, 500 hours or 90 days on lamp (whichever comes first) optional 5 years, 24/7 operation |

Last updated: 09 Jul 2024

© 2024 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.

