

MNA-120 ENC ANA

AV-to-IP encoder for the digital operating room with VGA & CVBS or VGA & S-Video



Barco's MNA series comprises adapters to encode and decode video, data and other information (e.g. control signals) to and from IP streams. These medically certified adapters ensure overall connectivity and support for current and legacy video sources. Automated device detection eliminates the need for user interventions when setting up the operating room.

Conversion to IP

The MNA encoders take in baseband video and non-video data and convert these to IP streams for transportation over a standard high-bandwidth IP network. The MNA decoders reconvert these raw IP packets to DVI video signals and other signals such as USB. End-to-end latency is amazingly short and is guaranteed not to exceed a single frame (< 15 ms).

The medical-grade MNA adapters offer:

- AV-to-IP conversion at the imaging source
- Complete connectivity for current and legacy video sources in the operating room, cath lab or interventional suite
- Support for non-video traffic (e.g. keyboard, mouse and audio)
- Easy integration via central API provided by Barco's NMS 1.0 software
- Smooth setup and ease of use

Product specificaties**MNA-120 ENC ANA**

General specifications	
Videoconversie	Converts to analog baseband video signals to uncompressed IP video streams
Beveiliging	AES 128 encrypted transmission of all video, data & control signals
Encoder-systeem	VGA & CVBS or VGA & S-Video
IP-connectiviteit	10GE Fiber Optic Interface with SFP+ connector module
IP-normen	AVB, IP, IGMP, IGMP snooping, PIM, RTP, RTCP, 802.1q, AES 128b, HTTP(s)
USB	USB OTG type A/B USB Type A
Audio	Line-in, line-out and mic-in connector
Naleving	Supporting HIPAA compliant external 12V Medical Approved PSU
Energieverbruik	< 30W
Grootte	37 mm H x152 mm W x152 mm D
Nettogewicht	Maximum 750 g
Geluidsniveau	Typical 38dBA at 20°C at 1m
Bedrijfstemperatuur	Range +5°C to +35°C Temperature change < 1°C/min
Opslagtemperatuur	Range -20°C to +60°C Temperature change < 1°C/min
Vochtigheid	Operational: 35°C / 85% RH non condensing Storage: RH + 40°C / 95% non condensing
Certificeringen	<ul style="list-style-type: none">■ CB (IEC 60601-1)■ CB (IEC 60950-1)■ cUL, UL (cULus)■ Demko■ CE medical device class I■ BIS Registration, IS 13252 (part 1)
Standaarden	Medical Equipment: <ul style="list-style-type: none">■ IEC 60601-1:2005 + Am1:2012■ IEC 60601-1-6:2010 + Am1:2013■ IEC 60601-1-2:2014 (ed4)■ ANSI/AAMI ES 60601-1: A1:2012 + C1:2009/(R)2012 + A2:2010/(R)2012■ CAN/CSA-C22.2 No.60601-1:14■ EN 60601-1:2006 + A1:2013 + A12:2014■ EN 60601-1-6:2010 + A1:2015■ EN 60601-1-2:2015 (ed4)■ FCC class B■ ICES-001 Level B ITE Equipment: <ul style="list-style-type: none">■ IEC 60950-1:2005 + Am1:2009 + Am2:2013■ EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011■ IS 13252

Laatst bijgewerkt: 18 Mar 2024

© 2018 Barco nv. Alle rechten voorbehouden. Gehele of gedeeltelijke reproductie zonder schriftelijke toestemming is verboden. Alle merknamen en productnamen zijn handelsmerken, geregistreerde handelsmerken of handelsnamen van hun respectieve houders. Vanwege voortdurende innovatie kunnen informatie en technische specificaties zonder voorafgaande kennisgeving worden gewijzigd. Raadpleeg www.barco.com voor de meest recente specificaties.