

RLM-W14

14,500 lumens, WUXGA, 3-chip DLP projector



- **Active Stereo 3D**
- **Video over a single Cat 5 cable**
- **Extended warping and blending**

Featuring a stylish projector design with a very stable lens mount, the RLM-W14 offers Active Stereo 3D and provides video over a single Cat 5 cable (HDBaseTTM). It is designed for fixed installation in museums, theaters, houses of worship, hotels, lecture halls or conference auditoriums; but its extended warping and blending, rugged chassis and optional rental frame make it equally suited for the rental market as well.

Video over a single Cat 5 cable

Supporting point-to-point transmission of video signals – up to WUXGA (1,920 x 1,200) at 60 Hz – from a source converter to a projector over a single Cat 5 cable, the RLM-W14's HDBaseTTM technology takes away the need for multiple cables and connectors, leading to more simplicity and lower costs.

Stunning images

Geared with three-chip DLP technology, the high-brightness RLM-W14 generates crisp and stable images with rich contrast and sensational colors. It also features a DICOM simulated mode that guarantees accurate greyscales and highly detailed images – key requirements for medical training.

Rugged design

Operating on a voltage of 110V - 240V, the RLM-W14 is a rugged projector that reduces noise and power consumption. Moreover, its TLD lenses are compatible with the RLM-W12, HDX and HDF projectors. It's also standard equipped with BarcoLink, allowing native WUXGA @60 Hz signals to be transmitted between the Barco image processors and projectors via a single BNC cable, for simple and reliable signal distribution.

- 14,500 lumens light output
- 3-chip DLP technology
- WUXGA (1,920 x 1,200) resolution
- Video over a single Cat 5 cable thanks to standard HDBaseTTM
- Standard Active Stereo 3D
- Extended warping and blending
- Better color stability & saturation
- Perfect for fixed installations
- Rental frame available
- Low power consumption
- Wide range of TLD lenses, compatible with RLM-W12, HDX, HDF and FLM projectors

Product specifications**RLM-W14**

General specifications	
Projector type	WUXGA 3-chip DLP digital projector
Technology	0.96" DMD™ x3
Resolution	1,920 x 1,200
Brightness	14,500 center / 13,500 ANSI lumens*
Contrast ratio	1,650:1 (standard) / 2,400:1 (CE)
Brightness uniformity	90%
Aspect ratio	16:10
ScenergiX	Horizontal and vertical edge blending
Lens type	TLD+
Lenses	0.73:1 ; 1.2:1 ; 1.16-1.5:1 ; 1.5-2.0:1 ; 2.0-2.8:1 ; 2.8-4.5:1 ; 4.5-7.5:1 ; 7.5-11.5:1
Optical lens shift	Vertical: -70% to +130% / Horizontal: +/-30% on zoom lenses memorized
Color correction	P7
Lamps	2x465W
Lamp lifetime	2,000 hours (typical) / 2,500 hours (maximum)
Lamp warranty	120 days, 500 hours
Sealed DLP™ core	Standard
Optical dowser	Standard
Picture-in-picture	Up to two sources simultaneously
Orientation	table -ceiling
WARP	preset values + custom (RS232)
Integrated web server	Yes
3D	Dual link DVI with sync in /out BNC
Inputs	HDMI (HDCP 1.3); HDBase-T; 5-BNC (RGBHV, RGBS/RGBsB;YUV); VGA (RGBHV, RGBS/RGBsB;YUV); cinch (RGBs, YUV); HSDI/ 3G HDSDI /SDI; 3D DUAL LINK DVI
Input resolutions	From NTSC up to UXGA (1,600 x 1,200), including HDTV (1,920 x 1,200)
Max. pixel clock	165Mhz up to 200Mhz
Software tools	Projection Toolset + Android app + iOS app
Control	Mini-jack + IR, RS232, 12v trigger
Network connection	10/100 base-T, RJ-45 connection
Power requirements	90-240V / 50-60Hz -1,140W @ 240V, 1,230W @ 110V, STBY less than 2W
Noise level (typical at 25°C/77°F)	46 dB(A) norm, 42dB(A) eco
Operational ambient temperature	0-40°C / 32°-104°F
Operational humidity	0-85% (non condens)
Dissipation BTU	max 4,131 BTU/h
Dimensions (WxLxH)	631 x 504 x 270 mm / 24.8 x 19.82 x 10.63 inches
Weight	33.5kg (73.8 lbs)
Shipping Dimensions	(LxWxH) 829 x 709 x 437 mm / 32.64 x 27.9 x 17.20 inches
Shipping Weight from Factory	41.5 kg (91.49 lbs)
Standard accessories	Power cord, wireless remote control, HDMI to DVI adaptor
Certifications	Complies with FCC rules & regulations, part 15 Class A and CE EN55022 Class A, CE, TUV, RHoS, WEE
Warranty	3 years standard, extra 2 years optional
*	+/-10%

Last updated: 16 Mar 2023

© 2018 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.