



- Up to 4K (3,840 x 2,400) resolution
- Durable and robust for 24/7 operation
- Improved motion Smear Reduction Processing (SRP)
- Long lifetime (up to 60,000 hours)

The F70-4K4, powered by Barco Pulse image processing, is an addition to the flagship F70 laser-phosphor series with native WQXGA and up to 4K (3,840 x 2, 400) resolution. It comes with improved performance for fast moving content, as well as improved color-to-white ratio, intended for high-demanding applications. Designed specifically for the simulation market's tough requirements it is robust and reliable, with an outstanding image quality.

24/7 operation for Low Total Cost of Ownership (TCO)

Designed for the motion platform's rapid and sudden movements, it is the perfect choice for any type of applications that need a robust visual system that last over time and can be operated 24/7. With a lifetime of up to 60,000 hours* coupled with long service intervals, the F70-series is one of the most durable projectors on the market and make sure the training time is maximized.

Optimized for smooth image performance

The F70-4K4's powerful and improved Motion Smear Reduction Processing (SRP) is optimized to remove the typical challenges occurring when viewing fast-moving content, e.g. when an aircraft is rolling, pitching, or banking. Combined with an improved color-to-white ratio, the user will experience increased brightness in colors, better color performance across moving images and deeper black levels for an impeccable reproduction of scenes. The SRP feature will also have a positive impact on lifetime.

With the Constant Light Output (CLOTM) functionality, the projector produces predictable, constant brightness and color over time. And thanks to Barco's unique and proprietary Single Step Processing (SSPTM) technology inherent in Barco Pulse, the F70 can perform several simultaneous processing intensive tasks, like running 4K resolution and warping/blending, without adding extra latency, providing a sharper and higher overall image quality.

BARCO

*Depending on the mode of operation

Product specifications	F70-4K4
General specifications	
Brightness	3,800 Lumens
Contrast ratio	1800:1 sequential, 50,000:1 dynamic
IR for NVG	no
Brightness uniformity	90%
Aspect ratio	16:10
Projector type	1DLP laser phosphor
Resolution	3,840 x 2,400 / 3,840 x 2,160 / 2,560 x 1,600 (native)
Lens type	FLD-series
Optical lens shift	Vertical up to 146%, depending on lens Horizontal up to 70%, depending on lens Motorized zoom and focus (+ lens memory FLDX lenses) Motorized lens shift (with position memory on all lenses)
Color correction	P7 RealColor TM
CLO (constant light output)	Yes
Light source	Laser phosphor
Light source lifetime	Up to 60,000 hours, depending on mode of operation
Sealed DLP™ core	Yes
Orientation	360° rotation, no restrictions
3D	Active stereoscopic 3D
Image processing	Embedded warp & blend engine (Barco Pulse)
Keystone correction	Yes
Inputs	HDSDI 2x DP1.2 2x dual link DVI-I HDBaseT HDMI2.0 (HDCP2.2, HDR10) RJ 45 Ethernet DMX in/out RS232 in 2x USB 12v out

Input resolutionsIncluding and up to: 3,840 x 2,400 @ 60Hz 3,840 x 2,400 @ 60Hz 3,840 x 2,160 @ 60Hz 4,096 x 2,160 @ 60Hz biplayPort: Including and up to 2560x1600@60Hz 8 bit RGB and 3840x2400@50Hz 8 bit RGBInput color depthDVI: Including and up to 2560x1600@60Hz 8 bit RGB and 3840x2400@50Hz 8 bit RGBSoftware toolsProjector ToolsetControlIR, R5232, RJ45Network connectionIR, R5232, RJ45Power requirements100-240V / 50-60HzPower consumption743 W nominal, 1100 W maximumBTU per hourMax 4,000 BTU/hNoise level (typical at 25°C/77°F)36 dB(A)Operating temperature10-40 °C (sea level)Storage temperature20 to 60 °COperating humidity10 -90% RHDimensions (WxLxH)475 x 593 x 286 mm / 18.7 x 23.3 x 11.2 inWeightTr (g / 81.5 lbs	Product specifications	F70-4K4
DisplayPort: Including and up to 2560x1600@120Hz 12 bit RGB and 3840x2400@60Hz 8 bit RGBSoftware toolsProjector ToolsetControlIR, RS232, RJ45Network connectionIR, RS232, RJ45Power requirements100-240V / 50-60HzPower consumption743 W nominal, 1100 W maximumBTU per hourMax 4,000 BTU/hNoise level (typical at 25°C/77°F)36 dB(A)Operating temperature10 -40 °C (sea level)Storage temperature-20 to 60 °COperating humidity20 -80% RHStorage humidity10 -90% RHDimensions (WxLxH)475 x 593 x 286 mm / 18.7 x 23.3 x 11.2 inWeight37 kg / 81.5 lbs	Input resolutions	3,840 x 2,400 @ 60Hz 3,840 x 2,160 @ 60Hz 4,096 x 2,160 @ 60Hz 2,560 x 1,600 @ 120Hz refresh rates: 24Hz to 120Hz for WQXGA (2560x1600) and 24Hz to 60Hz for 4K/4KUHD
ControlIR, RS232, RJ45Network connectionIR, RS232, RJ45Power requirements100-240V / 50-60HzPower consumption743 W nominal, 1100 W maximumBTU per hourMax 4,000 BTU/hNoise level (typical at 25°C/77°F)36 dB(A)Operating temperature10 -40 °C (sea level)Storage temperature-20 to 60 °COperating humidity20 -80% RHStorage humidity10 -90% RHDimensions (WxLxH)475 x 593 x 286 mm / 18,7 x 23,3 x 11,2 inWeight37 kg / 81,5 lbs	Input color depth	DisplayPort: Including and up to 2560x1600@120Hz 12 bit RGB and 3840x2400@60Hz 8
Network connectionIR, RS232, RJ45Power requirements100-240V / 50-60HzPower consumption743 W nominal, 1100 W maximumBTU per hourMax 4,000 BTU/hNoise level (typical at 25°C/77°F)36 dB(A)Operating temperature10 -40 °C (sea level)Storage temperature-20 to 60 °COperating humidity20 -80% RHStorage humidity10 -90% RHDimensions (WxLxH)475 x 593 x 286 mm / 18,7 x 23,3 x 11,2 inWeight37 kg / 81,5 lbs	Software tools	Projector Toolset
Power requirements100-240V / 50-60HzPower consumption743 W nominal, 1100 W maximumBTU per hourMax 4,000 BTU/hNoise level (typical at 25°C/77°F)36 dB(A)Operating temperature10 -40 °C (sea level)Storage temperature-20 to 60 °COperating humidity20 -80% RHStorage humidity10 -90% RHDimensions (WxLxH)475 x 593 x 286 mm / 18,7 x 23,3 x 11,2 inWeight37 kg / 81,5 lbs	Control	IR, RS232, RJ45
Power consumption743 W nominal, 1100 W maximumBTU per hourMax 4,000 BTU/hNoise level (typical at 25°C/77°F)36 dB(A)Operating temperature10 -40 °C (sea level)Storage temperature-20 to 60 °COperating humidity20 -80% RHStorage humidity10 -90% RHDimensions (WxLxH)475 x 593 x 286 mm / 18,7 x 23,3 x 11,2 inWeight37 kg / 81,5 lbs	Network connection	IR, RS232, RJ45
BTU per hourMax 4,000 BTU/hNoise level (typical at 25°C/77°F)36 dB(A)Operating temperature10 -40 °C (sea level)Storage temperature-20 to 60 °COperating humidity20 -80% RHStorage humidity10 -90% RHDimensions (WxLxH)475 x 593 x 286 mm / 18,7 x 23,3 x 11,2 inWeight37 kg / 81,5 lbs	Power requirements	100-240V / 50-60Hz
Noise level (typical at 25°C/77°F)36 dB(A)Operating temperature10 -40 °C (sea level)Storage temperature-20 to 60 °COperating humidity20 -80% RHStorage humidity10 -90% RHDimensions (WxLxH)475 x 593 x 286 mm / 18,7 x 23,3 x 11,2 inWeight37 kg / 81,5 lbs	Power consumption	743 W nominal, 1100 W maximum
Operating temperature10 -40 °C (sea level)Storage temperature-20 to 60 °COperating humidity20 -80% RHStorage humidity10 -90% RHDimensions (WxLxH)475 x 593 x 286 mm / 18,7 x 23,3 x 11,2 inWeight37 kg / 81,5 lbs	BTU per hour	Max 4,000 BTU/h
Storage temperature-20 to 60 °COperating humidity20 -80% RHStorage humidity10 -90% RHDimensions (WxLxH)475 x 593 x 286 mm / 18,7 x 23,3 x 11,2 inWeight37 kg / 81,5 lbs	Noise level (typical at 25°C/77°F)	36 dB(A)
Operating humidity 20 -80% RH Storage humidity 10 -90% RH Dimensions (WxLxH) 475 x 593 x 286 mm / 18,7 x 23,3 x 11,2 in Weight 37 kg / 81,5 lbs	Operating temperature	10 -40 °C (sea level)
Storage humidity 10 -90% RH Dimensions (WxLxH) 475 x 593 x 286 mm / 18,7 x 23,3 x 11,2 in Weight 37 kg / 81,5 lbs	Storage temperature	-20 to 60 °C
Dimensions (WxLxH) 475 x 593 x 286 mm / 18,7 x 23,3 x 11,2 in Weight 37 kg / 81,5 lbs	Operating humidity	20 -80% RH
Weight 37 kg / 81,5 lbs	Storage humidity	10 -90% RH
	Dimensions (WxLxH)	475 x 593 x 286 mm / 18,7 x 23,3 x 11,2 in
	Weight	37 kg / 81,5 lbs
Standard accessories Power cord, wireless remote control	Standard accessories	Power cord, wireless remote control
Certifications CE, FCC Class A and cNus	Certifications	CE, FCC Class A and cNus
Warranty Limited 5 years parts and labor, extendable	Warranty	Limited 5 years parts and labor, extendable

Last updated: 11 Oct 2023

© 2018 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.

BARCO