

RLM R6+ Performer

<P>SXGA+, 6,000 lumens three-chip DLP projector</P>



기술 사양

RLM R6+ PERFORMER

일반 사양

광 출력	6500 Center lumen 6000 ANSI Lumen												
해상도	1400 x 1050 (native)												
밝기 균일도	> 90% for the total screen												
명암비율	1600:1 (full field)												
디스플레이	3 Chip DLP SXGA+ (resolution of 1400 x 1050 pixels (aspect ratio 4:3)).												
컨버전스	Max allowed convergence drift is 0,5 pixel. This is checked on vertical and horizontal midlines only. Corners are not applicable for convergence error. This is measure with TLD 1.2 lens on axis.												
기능	<ul style="list-style-type: none"> ▪ AutoImage ▪ Advanced picture-in-picture ▪ Seamless switching with effects ▪ Standard light shutter ▪ Advanced digital zoom ▪ Rigging point ▪ Carrying handle ▪ Frame ▪ P7 color processing 												
PIP(Picture-in-picture)	Up to 4 sources simultaneously (2 data, 1 video and 1 SDI)												
입력	Fixed inputs <ul style="list-style-type: none"> ▪ 1x Configurable 5-Wire (BNC) ▪ 1x Composite Video (BNC) ▪ 1x S-Video (4-pin mini-DIN) ▪ 1x analogue RGB (D15 connector) ▪ 1x SDI/HDSDI (+ loop through) ▪ 1x DVI (Digital Visual Interface) 												
출력	HDSDI/ SDI loop out												
통신	<ul style="list-style-type: none"> ▪ 1x RS-232C IN (D-9 connector) ▪ 1x RS-232C OUT (D-9 connector) ▪ 1x RS-232C IN (XLR connector) ▪ mini-jack for wired remote control 												
호환성	<ul style="list-style-type: none"> ▪ All current video sources (PAL, SECAM, NTSC) in Composite, S-VHS, Component or RGB formats ▪ All currently proposed HDTV, extended and improved television standards (1080i, 720p) ▪ All computer graphics formats from VGA, SVGA, XGA, SXGA,full HD to UXGA ▪ Most Macintosh computers ▪ Electronic workstations with a resolution up to 1600 x 1200 pixels at 75 Hz ▪ Most computer sources with a pixel clock up to 200 MHz ▪ DVI sources up to SXGA+ 												
입력 소스 호환	1600 x 1200 (max. input)												
스크린 크기	From 1-7m / 3-23ft.recomended												
스캔 주파수	Pixel clock >162Mhz (UXGA 60hz)												
네트워크 연결	Optional (10 base-T)												
주위 온도	Max 40°C (104°F)												
램프	2 x 250 W mercury												
	Lamp warranty: 1000 hrs												
렌즈	<table border="1"> <thead> <tr> <th>Lens</th> <th>Order Nr</th> </tr> </thead> <tbody> <tr> <td>TLD (HB) 0.8</td> <td>R9842040</td> </tr> <tr> <td>TLD (HB) 1.6 - 2.0</td> <td>R9842060</td> </tr> <tr> <td>TLD (HB) 2.0 - 2.8</td> <td>R9842080</td> </tr> <tr> <td>TLD (HB) 2.8 - 5.0</td> <td>R9842100</td> </tr> <tr> <td>TLD (HB) 5.0 - 8.0</td> <td>R9842120</td> </tr> </tbody> </table>	Lens	Order Nr	TLD (HB) 0.8	R9842040	TLD (HB) 1.6 - 2.0	R9842060	TLD (HB) 2.0 - 2.8	R9842080	TLD (HB) 2.8 - 5.0	R9842100	TLD (HB) 5.0 - 8.0	R9842120
Lens	Order Nr												
TLD (HB) 0.8	R9842040												
TLD (HB) 1.6 - 2.0	R9842060												
TLD (HB) 2.0 - 2.8	R9842080												
TLD (HB) 2.8 - 5.0	R9842100												
TLD (HB) 5.0 - 8.0	R9842120												
렌즈범위	Vertical: -10% to +110% Horizontal: -50% to +50% (small differences occur per lens type)												
렌즈 인코더	On zoom and focus (with TLD lenses)												
ScenergiX	Standard horizontal and vertical electronic edge blending												
실드 DLP™ 코어	Standard												
먼지 필터	Metal filters												
소음도	42 dB(A) (at 40°C)												

기술 사양**RLM R6+ PERFORMER**

기본 전압	92-240 V / 50 -60 Hz
전력 소비	700 W
소비 전력	Max 2217 BTU/h
AC 전원	90V -255V (50 Hz -60Hz)
무게	Projector: 25 kg (56 lbs) Frame: 5 kg (11 lbs)
크기	W x L x H 705 x 707,8 x 316,5 mm (27.8 x 27.9 x 12.5 inch)
물품 크기	Width: 56 cm Height: 100 cm Depth: 100 cm Floor Space: 1 m ² Volume: 0,56 m ³ Gross Weight: 65 kg
안전 규정	Compliant with UL1950 and EN60950
전자파 장애	Complies with FCC rules & regulations, part 15 Class A and CE EN55022 Class A
주문 정보	Projector body (without lens): R9010270 Spare dual lamp: R9852940

작성일: 09 Jul 2024

© 2024 Barco nv. All rights reserved. 서면 허가 없이 전체 또는 부분을 복제하는 것은 금지됩니다. 모든 브랜드명 및 제품명은 상표, 등록 상표 또는 해당 소유자의 상표입니다. 지속적인 혁신으로 인해 정보 및 기술 사양은 사전 고지 없이 변경될 수 있습니다. 최신 사양은 www.barco.com을(를) 확인하세요.