PDS-4K Audio and DisplayPort 1.2 input card

- **Adds Audio pass-through and Dante capability to the system**

Adds the ability for the PDS-4K to pass embedded audio from HDMI™/DisplayPort/SDI input to Program outputs and embed/disembed to Dante network audio.

- **Adds two more input connectors**

Adds two DisplayPort 1.2 input connectors.

PDS-4K includes license from Audinate Pty Ltd under US Patents 7747725, 8005939, 7978696, 8171152, European Patent 2255541, Chinese Patent ZL200780026677.0 and other patents pending or issued, see www.audinate.com/patents

Consult the PDS-4K User Guide here.

Product specificaties	PDS-4K AUDIO AND DISPLAYPORT 1.2 INPUT CARD
General specifications	
Connectoren	2x DisplayPort 1.2 Inputs 2x RJ-45 (Dante)
Resolutie	3840x2400p @60
Kleurdiepte	10-bit
Kleursampling	4:4:4
HDCP	1.x
Signaalcapaciteit	660 MHz
Audiokanalen	2 per input or output
Audiosamplefrequentie	48 Khz
Audiobitdiepte	16bit or 24 bit
Audioformaat	PCM
AES 67-ondersteuning	Yes
Aantal Dante-kanalen	64 inputs x 64 outputs (2 channels per input or output)
Kenmerken	Outputs selectable between specific input, Dante Audio, or Audio follows video PGM audio return to Dante All inputs transmit to Dante

Laatst bijgewerkt: 19 Sep 2024

© 2024 Barco nv. Alle rechten voorbehouden. Gehele of gedeeltelijke reproductie zonder schriftelijke toestemming is verboden. Alle merknamen en productnamen zijn handelsmerken, geregistreerde handelsmerken of handelsnamen van hun respectieve houders. Als gevolg van voortdurende innovatie kunnen informatie en technische specificaties zonder voorafgaande kennisgeving worden gewijzigd. Controleer www.barco.com voor de nieuwste specificaties.