

# MXRT-1150

Compact PCIe x1 patient list display controller



**Product specifications****MXRT-1150**

General specifications	
Bus compatibility	Could be installed within PCI Express x1, x8, x16 mechanical slots Works in PCI Express x1, x4, x8, x16 electrical slots / operates at x1 speed
Power consumption	
Form factor	Low-profile, half-length (2.3"x 6.6")
Operating system	Windows® XP, X64, Vista
Platforms	Intel® and AMD architectures
Graphics accelerator	ATI FireMV™
Display memory	256 MB DDR2
Look up table	32 bits in / 32 bits out
Pixel depth	Up to 32 bit color
Electrical standard	DMS-59 to Dual DVI-I output
Connectors	DMS-59 to Dual DVI-I output
Supported resolutions	Analog: 2048x1536 Digital 1920x1200 per display VGA at boot-up
Approvals	FCC Class B, CE, ICES-003, VCCI, BSMI, MIC, UL
Operating temperature	0° to 55°C (32° to 131° F)

Last updated: 15 Mar 2023

© 2018 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check [www.barco.com](http://www.barco.com) for the latest specifications.