

Coronis Color 2MP (MFCD-2321)

2MP color flat panel display system



技术规格

CORONIS COLOR 2MP (MFCD-2321)

一般规格

显示技术	<ul style="list-style-type: none">TFT AMLCD - IPSColor
分辨率	2MP (1600 x 1200 / 1200 x 1600)
视角	170° (at 10:1 contrast)
暗室对比度	400:1 typical
亮度	<ul style="list-style-type: none">Max. luminance: 220 Cd/m² (64.2 fL)Calibrated luminance: 130 Cd/m² (37.9 fL)
稳定性, 校正和自动化质量控制	Embedded Color I-Guard
DVI	Complying to DVI 1.0
模拟	<ul style="list-style-type: none">VGA D-SUB15 connectorBNC (Monochrome only)
USB	USB 1.1 hub with 1 up-and 2 down stream ports, USB end point
支持分辨率	<ul style="list-style-type: none">1600 x 1200 (Landscape)1200 x 1600 (Portrait)VGA boot
认证	Safety: <ul style="list-style-type: none">CE, UL60950CSA C22.2 No. 60950 (c-UL)CBIEC 60950DEMKO EN 60950 Emission: <ul style="list-style-type: none">EN 55022 Limit A Immunity: <ul style="list-style-type: none">EN 50082-1 Medical: <ul style="list-style-type: none">FDA 510 k (Please contact factory for status)
人体工程学	<ul style="list-style-type: none">Tilt & swivel base with P/L rotations100 mm VESA mounting standardAR coated front cover

生成于: 09 Jul 2024

© 2024 巴可公司。保留所有权利。未经书面许可, 禁止全部或部分复制。所有品牌名称和产品名称均为其各自持有者的商标、注册商标或商号。由于不断创新, 信息和技术规格如有变更, 恕不另行通知。请查看www.barco.com.cn以了解最新规格。