

RLM H5 Performer

With its compact design and sealed optics, the RLM G5 Performer has proven itself to be an ideal all-round projector suitable to both the rental and staging markets.



Spécifications techniques

RLM H5 PERFORMER

Spécifications générales	
Luminosité	4500 ANSI Lumen
Résolution	1280 x 720 (native)
Taux de contraste	1000 : 1 (full field)
Mode contraste élevé	Available with special lenses
Uniformité de la luminosité	> 90%
Lampe	2 x 250 W mercury max. lifetime: 1500 hrs typ. lifetime: 1000 hrs min. lifetime: 750 hrs
Niveau sonore (à 20 °C -68 °F)	42 dBa
Niveau sonore (à 40 °C -104 °F)	46,5 dBa
Température ambiante	Max 40°C (104°F)
Consommation électrique	700 W
Tension secteur	92-240 V
Poids	Projector: 25 kg (56 lbs) Frame: 5 kg (11 lbs)
Dimensions (l x L x H)	705 x 707,8 x 316,5 mm
Obturbateur	Standard
Cœur de processeur DLP™ scellé	Standard
ScenergiX	Standard horizontal and vertical electronic edge blending
Commutation propre	Standard (wipes, fades, ...)
Image dans l'image	Up to 4 sources simultaneously (2 data, 1 video and 1 SDI)
Zoom numérique	Standard
Codeurs de lentilles	On zoom and focus (with TLD lenses)
Sortie lumineuse constante liée	not available
Compatibilité avec les sources en entrée	1600 x 1200 (max. input)
Entrées fixes	■ 1x configurable 5 cable (BNC) ■ 1x composite Video (BNC) ■ 1x S-Video (4-pin DIN) ■ 1x analogue RGB (D15 Connector) ■ 1x SDI/HDSDI (+ loop-through) ■ 1x DVI (Digital Visual Interface)
Entrées modulaires	not available
Contrôle	· 1 x RS-232 / 422 IN · 1 x RS-232 / 422 OUT · 1 x XLR female (2 way) · build-in RF remote transceiver (optional)

Spécifications techniques**RLM H5 PERFORMER**

Plage de décalage	Lens	Shift Range
	RLD 0.8	up-down: 35<>35 left-right: 15<>15
	Other RLD	up-down: 130<>40 left-right: 50<>50
	TLD (HB) 0.8	up-down: 90<>50 left-right: 40<>40
	Other TLD (HB)	up-down: 140<>50 left-right: 50<>50
Ratio de projection	Lens	Throw ratio
	RLD 0.8	0.64
	RLD 1.5 - 1.8	1.2 - 1.44
	RLD 1.8 - 2.25	1.44 - 1.8
	RLD 2.25 - 3.0	1.8 - 2.4
	RLD 3.0 - 4.5	2.4 - 3.6
	RLD 4.5 - 7.0	3.6 - 5.6
	TLD (HB) 0.8	0.8
	TLD (HB) 1.6 - 2.0	1.6 - 2.0
	TLD (HB) 2.0 - 2.8	2.0 - 2.8
	TLD (HB) 2.8 - 5.0	2.8 - 5.0
	TLD (HB) 5.0 - 8.0	5.0 - 8.0
Référence	R9010300	

Crée le : 15 Mar 2023

Les spécifications techniques sont susceptibles d'être modifiées sans préavis. Veuillez consulter les dernières informations disponibles sur www.barco.com.