

DX-100

Single-window video processor for LED displays



- Color calibration
- Genlocking
- DVI/(HD)SDI input and DVI/NNI output modules
- Wide variety of show effects

Product specifications

DX-100

General specifications

Input

- SDI
 - 8NTSC/PAL per SMPTE 259M
 - HD 720p per SMPTE 296M / HD 1080i per SMPTE 292M
 - DVI
 - RGB/YCbCr
 - All supported to maximum pixel rate: Single link (165MHz) / Dual link (240MHz)
-

Output

- Removable
 - NNI
 - Proprietary Barco format on an HDMI connector
 - Up to 2048 pixels either horizontally or vertically.
 - Maximum active area: 768K pixels
 - 12 bits per RGB per pixel
 - DVI
 - Proprietary Barco format on an DVI connector
 - Up to 2048 pixels either horizontally or vertically.
 - Maximum active area: 3x 480K pixels
-

Processing

- Number of layers: 1
 - Number of layers: 1
 - Ext. Genlock: Composite sync signal (standard or tri-level) or black burst. Termination is 75 ohms, +/- 0.1%.
 - Video Delay
-

Physical and Electrical

- Power Input: 100-240 VAC, 50-60 Hz
 - Power consumption: 180 watts maximum
 - Mechanical:
 - H: 8.75 inches (22.22 cm)
 - W: 17.00 inches (43.18 cm)
 - W: 19.00 inches (48.26 cm) with rackmount wings
 - D: 17.00 inches (43.18 cm), excluding connectors and latches
 - 5RU rackmount
 - Temperature: 0-40 degrees C
 - Humidity: 0-95% non-condensing
 - Chassis Weight: 52 lbs. (23.6 kg)
-

Last updated: 08 Jul 2024

© 2024 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.