

# Nio Gray 5.8MP (MDNG-6221)

5.8MP high-bright grayscale display



- Designed for radiology and 2D/3D mammography
- High-bright, adjustable tint grayscale
- I-Guard and QAWeb Enterprise for always-on compliance

Are you a radiologist specializing in reading breast cases in mainly grayscale modalities, such as 2D mammography and 3D tomosynthesis? If the answer is yes, then the Nio Gray 5.8MP is cut out just for you. It's fully up to date with capabilities and innovations for today's breast imaging, making this a modern display system that is efficient and easy for you to use. Furthermore, it's also perfectly suited for reading grayscale general radiology images in a comfortably high resolution.

## Bigger image, more details

Why 5.8MP? Well, in contrast to conventional 5.2MP display systems, you get 12% more pixels on your screen, which means that you can see more details at any given moment. Combine this with the tall 4:3 aspect ratio, which offers more room to view images in their entirety, and you get an ideal combo to start cutting back on additional panning and zooming.

## Reliable reading

The Nio Gray 5.8MP offers you more Just Noticeable Differences, thanks to its high brightness and contrast ratio. Our integrated stability, calibration and uniformity technologies make sure that image quality, light output and DICOM compliance remain consistent over the years.

## Efficient workflow

The Nio Gray 5.8MP is more than a grayscale monitor alone. It offers many ways to personalize settings to your liking, such as preferred tints of white or viewing angle. On top of that, it can help you improve your efficiency and speed, thanks to the set of Intuitive Workflow Tools included with our MXRT medical display controllers.

Did you know that SpotView, for example, makes it possible to make an area you



Did you know that SpotView, for example, makes it possible to make an area you choose twice as bright as it was originally? It's been proven to help radiologists reduce their reading time by as much as 15.5%. You can also define user profiles, saving you and your colleagues time. These automatically adjust the display in situations where it is shared by multiple people.

### Long lifetime, clear view

The Nio Gray 5.8MP adheres to the latest medical standards for medical devices in Europe & MQSA in the United States. It's also easy to install our free and highly secured QAWeb Enterprise application, with which you can rely on intervention-free, remote quality assurance. The tool makes it easy for PACS managers to centrally manage their Barco displays' uptime and compliance – anytime, anywhere.

To summarize, your Nio Gray 5.8MP monitor is a functional, easy-to-use diagnostic display system, fully up to date with today's innovations in general grayscale radiology, as well as 2D and 3D mammography. It comes with a 5-year warranty on its all components.

### Ensuring diagnostic confidence with MDR Class IIa

Our radiology displays are MDR-certified as Class IIa. Their product information has been reviewed and cleared by independent medical and technical experts, and is audited yearly. In other words, we ensure diagnostic confidence and peace of mind for our users.

### Technologies that enhance image quality:

- More detail on your screen, with 5.8MP resolution
- Designed to show breast images entirely, with 3:4 aspect ratio
- Increased contrast, with 1400:1 contrast ratio and 600 to 1000 cd/m<sup>2</sup> calibrated luminance
- Consistent brightness and grays, with Uniform Luminance Technology and SteadyGray
- Always stable DICOM images and auto QA, with I-Guard front sensor and optionally, QAWeb Enterprise
- Possibility to boost luminance, with I-Luminate and SpotView
- Optional settings and tools to adjust the monitor to your workflow, with Intuitive Workflow Tools

### A ecolabel for Nio Gray 5.8MP

The Nio Gray 5.8MP has been subjected to Barco's ecoscoring protocol and has received an A rating. Some key factors that contributed to this rating are:

- Energy efficient power supply, energy efficient standby and off modes
- Possibility to automatically switch to standby mode when device is not in use
- Halogen-free cables and plastics
- Use of recycled cardboard in packaging (>85% recycled content)
- Product design optimized for disassembly with common tools

**Product specifications****NIO GRAY 5.8MP (MDNG-6221)****General specifications**

Screen technology	LCD
Active screen size (diagonal)	541 mm (21.3")
Active screen size (H x V)	324 x 433 mm (12.77" x 17")
Aspect ratio (H:V)	3:4 for each display in portrait mode, 3:2 overall
Resolution	5.8 MP (2100 x 2800 pixels)
Pixel pitch	0.1545 mm
Gray imaging	Yes
Bit depth	10 bit
Viewing angle (H, V)	178°
Optical glass	MDNG-6221 option SPEF: Yes MDNG-6221 option SNEF: No
Uniformity correction	ULT
SteadyGray	Yes
Ambient light presets	Yes, reading room selection
I-Luminate	Yes
Ambient light sensor	MDNG-6221 option SPEF: Yes MDNG-6221 option SNEF: No
Front sensor	Yes
Maximum luminance	1300 cd/m <sup>2</sup> (MDNG-6221 SNEF / SPEF) 650 cd/m <sup>2</sup> (MDNG-6221 NC EM)
DICOM calibrated luminance	[MDNG-6221 SNEF / SPEF] Warranted maximum 1000 cd/m <sup>2</sup> Factory default 600 cd/m <sup>2</sup> [MDNG-6221 NC EM] 500 cd/m <sup>2</sup>
Contrast ratio (panel typical)	1400:1
Response time ((Tr + Tf)/2) (typical)	12.5 ms
Housing color	RAL 9003 / RAL 9004
Video input signals	DVI-D Dual Link (2x), DisplayPort(2x)
USB ports	1x USB 2.0 upstream (endpoint) 2x USB 2.0 downstream
Power rating	24 Vdc, 5 A; 5 Vdc, 0.1 A
Power requirements	This device shall only be powered by the medical approved power supply: Adapter Technology, type CMD160-P240: <ul style="list-style-type: none"><li>■ Input: 100-240 Vac, 50/60 Hz, 1.9-0.8 A</li><li>■ Output: 24 Vdc, 6.3 A; 5 Vdc, 0.5 A</li></ul>
Dimensions with stand (W x H x D)	Portrait: 378 x 528~628 x 235 mm Landscape: 491 x 472~572 x 235 mm
Dimensions w/o stand (W x H x D)	Portrait: 378 x 491 x 81 mm Landscape: 491 x 378 x 81 mm
Dimensions packaged (W x H x D)	500 x 280 x 670 mm
Net weight with stand	[MDNG-6221 SPEF] 11.6 kg [MDNG-6221 SNEF / NC EM] 10.2 kg
Net weight w/o stand	[MDNG-6221 SPEF] 6.6 kg [MDNG-6221 SNEF / NC EM] 5.2 kg
Net weight packaged	[MDNG-6221 SPEF] 17 kg (without optional accessories) [MDNG-6221 SNEF / NC EM] 15.7 kg (without optional accessories)
Tilt	-10° to 30°
Swivel	-45° to +45°
Pivot	90°
Height adjustment range	100 mm
Mounting standard	VESA (100 mm)
Screen protection	[MDNG-6221 SPEF] Hier wat tekst <ul style="list-style-type: none"><li>■ Available: yes</li><li>■ Anti-Reflective coating: yes</li><li>■ Material: glass</li></ul> [MDNG-6221 SNEF / NC EM] <ul style="list-style-type: none"><li>■ Available: no</li></ul>

## Product specifications

## NIO GRAY 5.8MP (MDNG-6221)

Recommended modalities	All digital images, including digital mammography and breast tomosynthesis.
Certifications	[MDNG-6221 SNEF / SPEF] CE0123 (Medical Device) FDA 510(K) K170476 CCC (China), KC (Korea), INMETRO (Brazil -Product Numbers: K9300370B, K9300372B), BIS (India), EAC (Russia, Kazakhstan, Belarus, Armenia and Kyrgyzstan) Safety specific: IEC 60950-1:2005+A1:2009+A2:2013 EN 60950-1:2006+A1:2010+A11:2009+A12:2011+A2:2013 IEC 62368-1:2018 EN IEC 62368-1:2020+A11:2020 IEC 60601-1:2005+A1:2012+A2:2020 EN 60601-1:2006+A1:2013+A12:2014+A2:2021 AAMI ES 60601-1:2005+A1:2012+A2:2021 CAN/CSA C22.2 No. 60601-1:2014 (Reaffirmed 2022) EMI specific: IEC 60601-1-2:2014+A1:2020 (Ed.4.1) EN 60601-1-2:2015+A1:2021 (Ed.4.1) FCC part 15 Class B ICES-001 Level B VCCI (Japan) Environmental: EU RoHS, China RoHS, REACH, Canada Health WEEE, Packaging Directive [MDNG-6221 NC EM] CE0123 (Medical Device) INMETRO (Brazil -Product Numbers: K9300371B), BIS (India) Safety specific: IEC 60950-1:2005+A1:2009+A2:2013 EN 60950-1:2006+A1:2010+A11:2009+A12:2011+A2:2013 IEC 62368-1:2018 EN IEC 62368-1:2020+A11:2020 IEC 60601-1:2005+A1:2012+A2:2020 EN 60601-1:2006+A1:2013+A12:2014+A2:2021 AAMI ES 60601-1:2005+A1:2012+A2:2021 CAN/CSA C22.2 No. 60601-1:2014 (Reaffirmed 2022) EMI specific: IEC 60601-1-2:2014+A1:2020 (Ed.4.1) EN 60601-1-2:2015+A1:2021 (Ed.4.1) Environmental: EU RoHS, REACH WEEE, Packaging Directive
Supplied accessories	<ul style="list-style-type: none"><li>■ User Guide</li><li>■ System sheet</li><li>■ Documentation disc</li><li>■ Video cable (1x DisplayPort)</li><li>■ Mains cable(s)</li><li>■ USB 2.0 cable</li><li>■ External power supply</li></ul>
Optional accessories	Display controller
QA software	QAWeb
Warranty	[MDNG-6221 SNEF / SPEF] 5 years, including 40000 hours backlight warranty [MDNG-6221 NC EM] 3 years, including 20000 hours backlight warranty
Operating temperature	0 °C to 40 °C (15 °C to 30 °C within specs)
Storage temperature	-20 °C to 60 °C
Operating humidity	8 % to 80 % (non-condensing)
Storage humidity	5 % to 85 % (non-condensing)
Operating pressure	70 kPa
Storage pressure	50 to 106 kPa

Last updated: 26 Jun 2025

© 2025 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check [www.barco.com](http://www.barco.com) for the latest specifications.