

F50 Panorama

Compact 120 Hz, single-chip DLP projector with Panorama resolution



- **Razor-sharp images with vivid colors**
- **Active 3D stereo and high frame rates**
- **Compact and rugged design**

Unmatched image quality

With its cutting-edge optics that deliver razor-sharp images, the F50 displays flawless images with vivid colors, and rich in contrast. Producing low noise levels, it also features RealColor™ color management, Smear Reduction Processing™ and high frame rates. The F50 boasts four different digital input sources and a wide range of expansion modules and high-quality projection lenses.

Key benefits

- Small, compact and ruggedized
- Ultimate reliability and low TCO
- Low operational noise level
- Active 3D stereo
- Smear Reduction Processing™/ 120Hz Refresh Rates / High Frame Rates

Product specifications**F50 PANORAMA**

| General specifications | |
|---------------------------------|--|
| Projector type | Single chip DLP digital projector |
| Technology | LVDS DMD™ with DarkChip3™ |
| Resolution | 2,560 x 1,080 |
| Brightness | 3,800 ANSI lumens (High Brightness) 1,900 ANSI lumens (VizSim Bright) 1,500 ANSI lumens (VizSim) |
| Contrast ratio | up to 5,300:1 |
| Brightness uniformity | >80% |
| Aspect ratio | 21:9 |
| Lens type | All pure glass lenses |
| Lenses | Ultra Wide Fixed EN53 (0.79:1 @1.65m) Wide Fixed EN52 (0.99:1) Super Wide Zoom EN55 (0.86 -1.16:1) Wide Zoom EN56 (1.14 -1.74:1) Zoom EN51 (1.71-2.37:1) Ultra short throw EN57 (0.3:1) |
| Optical lens shift | Vertical: +212%; Horizontal: +/-72% (lens dependant) |
| Color correction | RealColor™ |
| Lamps | 1 x 350W UHP (dimnable) |
| Lamp lifetime | Up to 2,000 hours (Full power)/up to 2,500 hours (Eco mode) |
| Lamp house, quick replace | Yes |
| Lamp warranty | 500 hours or 90 days |
| Sealed DLP™ core | Yes |
| Orientation | Table -ceiling (360 degrees through lamp axis) |
| 3D | Up to 2,560 x 1,600 @ 120Hz |
| Inputs | 2x DisplayPort 1.2 (HBR2), 1 x DVI-Dual Link, 1 x HDMI 1.4a, 1 x VGA, 2x 3G-SDI, 1x HDBaseT |
| Input resolutions | 2,560 x 1,600 -640 x 480 pixel resolution, RGBHV, RGBS, RGsB, custom formats available, HDTV (1080p, 1080i, 720p), NTSC, PAL, SECAM |
| Max. pixel clock | Up to 600 Mhz (2,560 x 1,600@120 Hz max) DP 1.2 Up to 330 Mhz Dual link DVI |
| Software tools | SimCAD, Projector Toolset |
| Control | IR, RS232, Ethernet, USBA, 2x BNC sync, 1x MiniDIN |
| Network connection | 10/100/1000 base-T, RJ-45 connection, RS-232 |
| Power requirements | 100-240V 50-60Hz |
| Power consumption | less than 530W |
| Operational ambient temperature | 10 -40 °C /50 -104 °F, 0-3,000m (Storage temperature: -20 -60 °C/-4 -140 °F) |
| Operating humidity | 20 -80% RH (Storage Conditions: 10 -90% RH) |
| Dissipation BTU | max 1,807 BTU/h |
| Dimensions (WxLxH) | 342 x 306 x 143 mm / 13.46 x 12.05 x 5.63 in |
| Weight | 7.5 kg / 16.5 lbs |
| Standard accessories | Power cord, wireless remote control |
| Certifications | Compliant with FCC, part 15 Class A and CCC, cNus, cUL, UL and CE |
| Warranty | Limited 3 years parts and labour |

Last updated: 13 Jun 2023

© 2018 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.