

OverView cPR84 (Atlas CS4)

84" Display Wall system integrating 3-panel Poly-Silicon LCD technology with SXGA resolution.



Product specifications**OVERVIEW CPR84 (ATLAS CS4)****General specifications**

Resolution	SXGA
Aspect ratio	5:4
Colors	16.7 millions
Lamp	<ul style="list-style-type: none">• 100 Watt lamp• operation time 8,000 hours (average)
AC power	95-230 VAC \pm 10%, 50-60 Hz
Power	220 W
Luminance	110 cd/m ² 32 ftL
Brightness	500 lumens
Contrast	350:1
Brightness uniformity	> 95%
Dimensions structure	<ul style="list-style-type: none">• Diagonal 84"• Width 1650 mm / 65 in.• Height 1320 mm / 52 in.• Footprint 1078 mm / 42.5 in.• Depth 1225 mm / 48.2 in.• Socket height min 366 mm / 14.4 in.
Environmental Compliance	<ul style="list-style-type: none">• Operating temperature: 17 °C -27 °C or 62 °F -80 °F• Humidity: recommended 40% -60%, non condensing Typical for stitched screens.
Screens	<ul style="list-style-type: none">• high gain screens for high brightness and high contrast• other screens on request

Last updated: 09 Jul 2024

© 2024 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.