

S3-4K Jr Gen 2

Compact and cost-effective Event Master processor



The updated S3-4K Jr Gen 2 configuration is ideally suited for applications that do not require the full capacity of the S3-4K Gen 2 or E2 Gen 2. It comes configured with one Gen 2 input cards, two output cards, a 4K60 MVR and two mixers on an up to 4Kx2K canvas in the same 3 RU form factor as its bigger S3-4K Gen 2 brother. S3-4K Jr Gen 2 can easily grow with your shows through upgrades. Simply purchase and install additional cards into your system. With all cards installed you can even upgrade the S3-4K Jr Gen 2 to a fully loaded S3-4K Gen 2 system at any time.

Powerful features, easy operation

- Pre-loaded with six I/O cards
- Interlinking of S3-4K chassis allows expansion of inputs, outputs or layers
- Manage all versions of the system with the cross-platform Event Master Toolset
- Serviceable in the field and ready for future signal interfaces via the modular Event Master cards
- Optional dual redundant power supply for maximum peace of mind
- Projection blend and Native Test Pattern support
- LED Custom format and Native Test Pattern support

Product specifications**S3-4K JR GEN 2**

General specifications	
Live effects canvas	-10 Megapixels PVW/PGM -20 Megapixels PGM only
Video inputs	6 FHD@60 inputs via 1 Tri-combo card <ul style="list-style-type: none">■ Mix and match between 6 x FHD@60 to 2x 4K@60 inputs■ 4x SD/HD/3G/6G/12G SDI connectors (Tri-Combo card)■ 1x HDMI 2.0 (600MHz max)■ 1x DisplayPort 1.2 (660MHz max)
Video outputs	8x FHD@60 /12x 4K@30 / 6x 4K@60 outputs via 2 output cards (HDMI 2.0 4 outputs ea) <ul style="list-style-type: none">■ Multiviewer 4x HDMI 2.0 for 4x FHD@60 or 1 x 4K60 (600MHz max)■ 4x HDMI 2.0 when used as standard output card
Genlock	Analog reference input/loop on BNC connectors; bi-level and blackburst at SD and tri-level at HD S3D Sync: 4x input Din connector, 2x output Din connector
Program output	<ul style="list-style-type: none">■ Up to 4 program outputs with mixing background and pip/key, configurable as single screens or tiled/blended widescreens (preview and Multi-Viewer not available in all configurations)■ Configurable for up to 8 x 4K@30 / 4 x 4096x2400@60■ Independent edge blending/feathering control for all four sides
Scaled Aux outputs	<ul style="list-style-type: none">■ Route and Scale any source to any Auxilliary output■ User definable for up to 8 x 4K@30 / 6 x 4096x2400@60■ All outputs can be defined as Aux destinations for a total of 8 Aux outputs■ Output color correction. (preview and Multi-Viewer not available in all configurations)■ Upscale any source to any Super AUX array of screens
Mixers	<ul style="list-style-type: none">■ Native resolution background mixer per program screen■ Independent layer transitions or full Preview/Program transition■ Flexible layer allocation – 2 mixable or 4 single scalable PIP/key layers assignable to any Program output screens.
Still stores	Up to 100 HD or 25 UHD. Import file size dependent.
Layer effects	<ul style="list-style-type: none">■ Borders (hard, soft, halo) and drop shadows■ Color effects■ Strobe, H&V flip■ Luma, chroma and Cut/Fill keys (not all modes support keying)■ PIP moves via Keyframes
Multiviewer	<ul style="list-style-type: none">■ Flexible user-definable layouts■ Monitor all Inputs and Outputs, including Preview and Aux■ 4 x FHD@60 outputs or 1 x 4K60■ Dedicated hardware same as E2 Gen2 Event Master Processor■ Source On Pvw/Pgm Indication in MVR■ Source on PVW/PGM reflected in the operation view■ Source on PVW/PGM available via TSL3.1 on network
Expandability	Linking is available as an user upgradeable option via adding Link Card.

Product specifications**S3-4K JR GEN 2**

HDCP	HDCP Compliance determined by installed cards.
Control	<ul style="list-style-type: none">■ Event Master screen management software for PC or MAC■ Event Master Controllers■ WebUI■ JSON and Telnet API available■ Ethernet RJ-45, 1000/100/10 Mbps autosense
Serviceability	<ul style="list-style-type: none">■ Field-Serviceable I/O and processing cards (not hot-swappable)■ Hot swappable power supplies, Optional redundant.
Noise Level	<ul style="list-style-type: none">■ Max 51.3 dB avg. Fans at 100%■ As low as 34 dB with low fanspeed■ Fan speed is software managed based on operating temperature■ Reference ISO 7779
Dimensions	<ul style="list-style-type: none">■ Height: 13.26 cm / 5.22 inches - 3 RU Rackmount■ Width: 43.2 cm / 17 inches without chassis handles, 48.3 cm / 19 inches with chassis handles attached■ Depth: 54 cm / 21.33 inches overall
Weight	21 kg / 46 lbs
Power	Input power: 100-240Vac, 50/60Hz, 8.8A (x2), 826 Watt Ships with single power supply. Optional Dual-redundant, hot-swappable power supplies; available as upgrade.
Warranty	3 years parts and labor
Environmental temperature	0-40 C (32-104 F)
Environmental humidity	0-95% non-condensing (non-operating) 0-85% non-condensing (operational)

Last updated: 22 Jun 2023

© 2018 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.