

iCon H600

Network-centric, 1080p HD, 6,000 lumens LCD projector



Product specifications**ICON H600**

General specifications	
Light output	6000 ANSI lumens
Resolution	HD 1080 (1920x1080px)
Brightness uniformity	> 95 % for the total screen
Contrast ratio	> 800:1 (full white/full black)
Display	3 x 1.65" polysilicon LCD panel with native HDTV resolution (1920 x 1080 pixels)
Features	<ul style="list-style-type: none">■ AutoImage■ Advanced picture-in-picture■ Standard cable basket■ Advanced digital zoom■ Advanced Desktopintegration
Picture-in-picture	Background desktop image + up to 4 sources simultaneously (data or video)
Inputs	Standard: <ul style="list-style-type: none">■ Layer 1: RGBHV or Component input; Composite video input; S-Video input■ Layer 2: RGBHV or Component input; Composite video input; S-Video input■ Layer 3: DVI input and D15 input■ Layer 4: Available for optional inputs Optional: The following input boards can be placed on any of the 4 layers: <ul style="list-style-type: none">■ RGBHV or Component input; Composite video input; S-Video input■ DVI input and D15 input■ SDI and HDSDI input and loop trough
Outputs	DVI out (1920 x 1080 at 60 Hz) of full screen composed image (including window inserts)
Communication	<ul style="list-style-type: none">■ 1x RS-232C (D-9 connector)■ mini-jack for wired remote control
Compatibility	<ul style="list-style-type: none">■ All current video sources■ All current HDTV sources■ All computer graphics sources with a pixel clock up to 275 Mhz (VGA, XGA, SXGA, SXGA+, UXGA, QXGA:2048x1536)■ DVI up to UXGA and HDTV resolution■ HD-SDI, SDI optionally available
Input source compatibility	2048 x 1536 @ 56Hz max input
Screen size	From 1-6m / 3-20ft.
Scan Frequencies	Horizontal 15kHz -110 kHz Vertical 25 Hz -150 Hz
Network connection	2 x 10/100/1000 Base-T Ethernet
On board display server	<ul style="list-style-type: none">■ Provides native 1920 x 1080 resolution■ Pentium 4 2,6 Ghz, 1 Gigabyte DDR RAM, 40 Gigabyte harddisk (upgradeable)■ 2 x PCMCIA slot for Wireless LAN cards, memory cards, extensions for inputs and outputs, Bluetooth■ 2 USB connectors and PS2 connector■ 2 x 10/100 Mb/s Ethernet RJ 45 connector■ 1x RS-232C (D-9 connector)■ Included software:
Ambient temperature	5°C up to 40°C
Lamp	2 x 300 Watt UHP lamp Lifetime: 1500 h/lamp

Product specifications**ICON H600**

Lenses	<ul style="list-style-type: none">• Fixed lenses:<ul style="list-style-type: none">-QGD (0.86:1) R9840491-QFD (1.27:1) R9840400-QFD (2.5:1) R9840290-QFD (7.0:1) R9840410• Zoom lenses:<ul style="list-style-type: none">-QHD (1.4 -2.0:1) R9849930-QHD (2.1 -3.0:1) R9849810-QFD (3.4 -4.5:1) R9840060-QFD (4.5 -6.0:1) R9840100
Lens Shift	Vertical: -120% to +120% Horizontal: -50% to +50%
Dust filters	Dense High Quality Microfilter (front side removeable)
Noise Level	< 39 dB
Mains Voltage	90V-255V
Power consumption	Max. 900 Watt
Power Dissipation	Max. 2900 BTU/hour
AC power	90V -255V (50 Hz -60Hz)
Weight	35 kg (77 lbs)
Dimensions	D x W x H, without cable basket: 679 x 567 x 282 mm (26.73 x 22.32 x 11.10 inch)
Safety Regulations	Compliant with UL1950 and EN60950
Electromagnetic Interference	Compliant with FCC rules & regulations, part 15 Class A, CE EN55022 Class A and CCC

Last updated: 15 Mar 2023

© 2018 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.