

iCon H250

Network-centric, 1080p HD, 2500 lumens single-chip DLP projector



Technische Daten

ICON H250

Allgemeine technische Daten

Lichtausgabe	2500 ANSI lumens
Auflösung	1920 x 1080 (native)
Helligkeitsgleichförmigkeit	> 95% for the total screen
Lampe	2x 250 Watt P-VIP lamp in lamp housing, pre-aligned for max. light output. Typical lifetime: 1,500 h/lamp
Optiken	Sealed optical engine
Kontrast	> 2000:1 (full white/full black; depending on lens, focus and projector settings)
Display	1-chip 0.95" DarkChip3® DLP™ 1080p panel with BrilliantColor™ processing and a native HDTV resolution of 1920 x 1080 pixels, 16:9 aspect ratio
Farbrad	RGBRGB
Merkmale	<ul style="list-style-type: none">■ Advanced picture-in-picture (PiP)■ Intelligent dual lamp system■ On board PC with Windows OS for network centric operation■ Advanced desktop integration (source and PiP handling through Windows OS)■ Sealed optical engine■ Standard cable basket
Eingänge	<ul style="list-style-type: none">■ 1x Component video, RGBHV, RGBS or RGsB (5x BNC)■ 1x Composite video (BNC)■ 1x S-video (4-pin mini-DIN)■ 1x VGA (D15 connector)■ 2x DVI-D (Digital Visual Interface-Digital)
Ausgänge	<ul style="list-style-type: none">■ 1x DVI-D
Kompatibilität	<ul style="list-style-type: none">■ All current video sources in composite, S-video, component or RGB formats■ All current HDTV sources (720p, 1080i)■ All computer graphics sources with a pixel clock up to 270 Mhz (VGA, S-VGA, XGA, SXGA, SXGA+, UXGA, QXGA: 2048x1536)■ DVI sources up to UXGA and HDTV resolution■ Apple Macintosh formats
Frequenzen	Horizontal 15kHz -140kHz Vertical 25Hz -150Hz
Kommunikation	<ul style="list-style-type: none">■ 1x D9 connector for RS-232■ 1x IR remote receiver■ 4x USB■ 1x RJ45 ethernet■ 1x PCMCIA slot (Type II)
Bildgröße	From 1.2 -6m / 4 -20ft
Lens Shift	Max. vertical shift from -25% to +140% (with QCLD 0.85:1 lens: +/-25%)
Onboard-Display-Server	<ul style="list-style-type: none">■ Pentium M 1.6 GHz processor■ 1 GB RAM■ 40 GB harddisk (5,400 rpm)■ Microsoft™ Windows XP™ Professional Multi-language OS installed■ Barco Server software for network communication between display server and clients■ DropZone software■ Proximity Desktop client software■ Remote Control & Diagnostics software
Stromverbrauch	Max. 730 Watt
Stromversorgung	Power factor pre-regulated SMPS, 90-254 VAC / 50-60Hz
Sicherheitsstandards	Compliant with ETL60950 and EN60950
Elektromagnetische Interferenz	Compliant with FCC rules & regulations, part 15 CE EN55022 Class A and CCC
Abmessungen	Projector body with cable basket: W 415 mm (16.34") x H 195 mm (7.68") x D 565 mm (22.24") Without cable basket: D = 487 mm (19.17") Including lens: Dmax = 590 mm (23.23")
Gewicht	Net weight, body only: 16 kg (35.3 lbs) Shipping weight: max. 20 kg (44.1 lbs)

Generiert am: 09 Jul 2024

© 2024 Barco nv. Alle Rechte vorbehalten. Die vollständige oder teilweise Reproduktion ohne schriftliche Genehmigung ist nicht gestattet. Alle Markennamen und Produktnamen sind Marken, eingetragene Marken oder Handelsnamen ihrer jeweiligen Inhaber. Aufgrund fortlaufender Innovationen können sich Informationen und technische Spezifikationen ohne vorherige Ankündigung ändern. Die neuesten Spezifikationen finden Sie unter www.barco.com.