


BarcoMed 2MP2FH

Dual-head 2MP medical display controller



Product specifications**BARCOMED 2MP2FH****General specifications**

Bus	PCI 2.1 & 2.2, universal signaling
Bus clock speed	33Mhz
Bus width	32 bit
Power consumption	< 15 Watt
Form factor	106 x 197 x 16 mm (4.2 x 7.6 x 0.6")
Operating system	Microsoft Windows NT4, 2000, XP
Platforms	Pentium class and up
Display configuration	Single-or dual-head, portrait or landscape
Graphics processor	Proprietary AURA technology
Display memory	32 Mb
VGA	<ul style="list-style-type: none">■ Integrated VGA controller■ Also compatible with external VGA cards
Pixel clock rate	120 Mhz
Look up table	10 bits in / 10 bits out
Electrical standard	Dual DVI complying to VESA DVI Rev. 1.0 spec
Supported resolutions / refresh rates	<ul style="list-style-type: none">■ 1280 x 1024 @ 60 Hz■ 1024 x 1280 @ 60 Hz■ VGA at boot-up
Connectors	Two DVI connectors (one per head)
Operational temperature	+10°C to +60°C (50°F to 140°F)
Storage temperature	-40°C to +85°C (-40°F to 185°F)
Operating humidity	80%
Storage humidity	100%
EMI	<ul style="list-style-type: none">■ FCC class A, CE■ EN 55022 A, EN 50082-1

Last updated: 09 Jul 2024

© 2024 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.