


OverView OVD5521

55" near-seamless LCD video wall for high-end applications



Barco's OverView OVD5521 is a high-performance, high brightness (700 cd/m² typical) 55" LCD-panel, dedicated for use in tiled video wall applications. With an extremely narrow bezel of 3.5 mm (0.14"), excellent colors and contrast, and a wide viewing angle, the OverView OVD5521 takes the visual performance of LCD video walls in high-end control rooms to a new level. Boosting very high brightness levels, the OverView OVD5521 remains clearly readable whatever the room's lighting conditions.

Its best in class temperature sensor controlled heat management system, uses ultra low noise fans to ensure optimal cooling at all time, maximizing the backlight's lifetime. Additional innovations and low power consumption ensure this panel delivers maximal image quality at a minimal TCO.

Saving costs with automatic color and brightness calibration

All the different screens in a tiled LCD video wall need to be perfectly balanced in terms of colors and brightness, so regular calibration is essential. As the first and only manufacturer, Barco now introduces its SenseX automatic color and brightness calibration system, that lets you calibrate the complete wall within minutes, without any external sensor or manual intervention.

Available as Instant VideoWall bundle

Barco also offers complete packages, containing four, six or eight OverView OVD5521 displays to create a 2x2, 3x2 or 4x2 video wall respectively, complete with wall mounts and cables. Optionally, you can bundle it with a controller, and software. In this way, you have your completely configured video wall solution in one package.

Product specificaties

OVERVIEW OVD5521

Panel	
Lcd-technologie	SPVA
Resolutie	Full HD (1920 x 1080)
Achtergrondverlichting	Direct LED
Beeldverhouding	16:9
Pixeldichtheid	40 dpi
Vernieuwingssnelheid	60 Hz
Luminantie	700 cd/m ² (typ.)
Contrast	3500:1 (typ.)
Kijkhoek	H 178° V 178°
Wit punt	10,000 K
Kalibratie	Sense X automatic color and brightness calibration
Levensduur van de achtergrondverlichting	60,000 h (typ)
MTBF	100,000 h (half brightness)
Koeling	Ultra low noise fans
Schermevel	44%
Bedrijfstemperatuur	0-40°C
Vochtigheid in bedrijf	10-80% non-condensing
Stoffilters	ISO 14644-1 ISO class 8
Opslagtemperatuur	-20°C-60°C
Vochtigheid bij opslag	5-95% non-condensing
Dimensions	
Afmetingen	1213 x 684 x 98.2 mm 47.8" x 26.9" x 3.87"
Actief scherm (diagonaal)	54.6" (1388 mm)
Actief schermgebied	1210 mm x 680 mm 47.63" x 26.79"
Gewicht	29.2 kg
Totale breedte van omlijsting (twee aangrenzende beeldschermen)	3.5 mm 0.14"
Connectivity	
DVI	2 inputs
Afstandsbediening	External dongle with approx. 1m 3.5mm Stereo Male to IR Receiver
OPS (Open Pluggable Specification)	Yes
DisplayPort	1 input/output
Ethernet-poort	2
HDCP	Yes
HDMI	1 input
USB	1 input (USB 2.0)
Power	
Ingangsspanning (wisselstroom)	100-240 VAC, 50-60 Hz
Energieverbruik	Typ: 140 W Max: 260 W
Warmteafvoer	Typ: 478 BTU/h Max: 888 BTU/h
EnergyStar	Full wall EnergyStar

Laatst bijgewerkt: 08 Jul 2024

© 2024 Barco nv. Alle rechten voorbehouden. Gehele of gedeeltelijke reproductie zonder schriftelijke toestemming is verboden. Alle merknamen en productnamen zijn handelsmerken, geregistreerde handelsmerken of handelsnamen van hun respectieve houders. Als gevolg van voortdurende innovatie kunnen informatie en technische specificaties zonder voorafgaande kennisgeving worden gewijzigd. Controleer www.barco.com voor de nieuwste specificaties.

