

iD Pro R600

The smartest and brightest network centric single-chip DLP projector with SXGA+ resolution and an amazing brightness level of 6,000 ANSI lumens.



Technische Daten

ID PRO R600

Allgemeine technische Daten

Lichtausgabe	6,000 ANSI lumens
Auflösung	SXGA+ (1400 x 1050)
Helligkeitsgleichförmigkeit	> 95 % for the total screen
Kontrast	2,000 : 1 (full white/full black)
Display	1-chip 0.95" DarkChip3™ DLP™ SXGA+ panel, with a native resolution of 1400 x 1050 pixels, 4:3 aspect ratio
Merkmale	<ul style="list-style-type: none">■ AutoImage■ Advanced picture-in-picture■ Seamless switching with effects■ Standard cable basket
Bild-im-Bild	Up to 3 sources simultaneously
Eingänge	<ul style="list-style-type: none">■ 1x Component Video (RGBHV, RGBS or RGsB (5 BNC))■ 1x Composite Video (BNC)■ 1x S-Video (4-pin mini-DIN)■ 1x VGA (D15 connector)■ 1x DVI (Digital Visual Interface)■ 1x SDI optional <p>Audio connections:</p> <ul style="list-style-type: none">■ 1x Stereo mic in■ 1x Stereo line in■ 1x Stereo line out
Ausgänge	No output
Kommunikation	1x D9 connectors for RS232 In/Out 1x spherical IR receiver
Kompatibilität	<ul style="list-style-type: none">■ All current video sources (PAL, SECAM, NTSC) in Composite, S-VHS, Component or RGB formats■ All currently proposed HDTV, extended and improved television standards (1080i, 720p)■ All computer graphics formats from VGA, SVGA, XGA, SXGA to UXGA■ Most Macintosh computers■ Electronic workstations with a resolution up to 1600 x 1200 pixels at 75 Hz■ Most computer sources with a pixel clock up to 160 MHz■ DVI sources up to SXGA+
Eingangquellenkompatibilität	1600 x 1200 (max. input)
Bildgröße	From 1-6m / 3-20ft.
Frequenzen	Horizontal 15kHz -110 kHz Vertical 25 Hz -150 Hz
Netzwerk-Verbindung	1 x 10/100 Base-T Ethernet
Onboard-Display-Server	Server Specifications: -Processor: Pentium M 1.6 GHz -Memory: 512 MB DDR RAM -Storage: 40 GB hard disk -Inputs and outputs: <ul style="list-style-type: none">■ PCMCIA slot for Wireless LAN cards, memory cards, Bluetooth, input extensions ...■ RJ45connector for Ethernet (10Mb/s) and Fast Ethernet (100Mb/s)■ 4 USB connectors■ Audio: 3,5 mm jacks for Microphone in, Line in and Line out
Umgebungstemperatur	5°C up to 40°C
Lampe	2 x 250 Watt UHP lamp, in lamp housing, pre-aligned for max. light output. Typical lifetime: 1,500 h/lamp. 1,500 hours in Dual Lamp Mode or 3,000 hours in Single Lamp Mode.
Optiken	Fixed focal length lens with a throw ratio of 0.8:1 Variable focal length lenses with a throw distance of 1.1-1.3, 1.2-1.6, 1.6-2.4, 2.4-4.3 times the screen width
Lens Shift	Motorized V shift: -30% +110%
Objektiv-Encoder	For specific details per lens type: see lens product pages
ScenergiX	Not Applicable
Gekapseltes optisches System	Not Applicable
Staubfilter	High Quality Microfilter (side removeable)
Geräuschpegel	< 41 dB
Netzspannung	90V-255V
Stromverbrauch	Max. 680 Watt
Wärmeabgabe	Max. 2400 BTU/hour
Stromversorgung	Power factor pre-regulated SMPS, 90-254 VAC / 50-60Hz
Gewicht	Net weight: body only: 13.5 kg/29.8 lbs
Abmessungen	Projector body with cable basket: 415 mm (max. W) x 195 mm (max. H) x 565 (max. D) Projector body without cable basket: 415 mm(max. W) x 195 mm (max. H) x 487 (max. D)
Sicherheitsstandards	Compliant with UL1950 and EN60950
Elektromagnetische Interferenz	Compliant with FCC rules & regulations, part 15 Class B, CE EN55022 Class B and CCC

Generiert am: 09 Jul 2024

© 2024 Barco nv. Alle Rechte vorbehalten. Die vollständige oder teilweise Reproduktion ohne schriftliche Genehmigung ist nicht gestattet. Alle Markennamen und Produktnamen sind Marken, eingetragene Marken oder Handelsnamen ihrer jeweiligen Inhaber. Aufgrund fortlaufender Innovationen können sich Informationen und technische Spezifikationen ohne vorherige Ankündigung ändern. Die neuesten Spezifikationen finden Sie unter www.barco.com.