

# Valkyrie



The Vikings believed the Northern Lights in the sky were the reflections of the Valkyries' armor as they led the warriors to Odin. We see our Valkyrie as the solution that will lead customers to Barco, to experience what a great image is.

## Aiming for the optimal experience

Valkyrie is Barco Residential's most popular LED solution based on size and viewing distance. You would think 1.2 pixel pitch is big, but LED is about the correct viewing and about how the source is delivered from the content player to the display. Barco is always making sure the image is perfect. We have developed a completely new processor for our Valkyrie display, which reproduces a revolutionary viewing experience with an highly dynamic, yet very realistic image.

## Part of the TruePix Northern Lights range

TruePix is Barco's flagship indoor high-resolution LED platform. The 27,5" inch tiles with a 16:9 aspect ratio range from .9mm to 1.5mm pixel pitch. TruePix brings content to life as intended and ensures predictable, truly seamless visualization, based on smart engineering and the company's next-generation Infinipix® gen2 image processing platform. This ensures color accuracy and perfect contrast at any brightness level. The self-regulating wall structure and perfectly aligned LED modules offer a perfectly flat wall and uniform image, with seams less than 0.1 mm, the entire video wall lifetime.

## LED for the residential market

With more than 2 decades of expertise on LED technology, Barco is not new to the LED market. But it is the first time we introduce that expertise, knowledge and experience into the Residential market. To be true to our philosophy to make sure we share the movie director's passion and commitment to the 'suspension of disbelief', which is so important in the art of movie-making, we have made sure TruePix supports the most common color gamuts used in our Market. Our products support both REC 709 and DCI color space as well as the latest HDR technologies.

**Product specifications****VALKYRIE**

General specifications	
Resolution	3840 x 2160
Pixel pitch	1.2
Pixel per module	480 x 270 (HxV)
Number of tiles	64
Brightness	>600 Nits
Brightness uniformity	>98%
Image processing	23 bit
Color depth	16 bit (281 trillion colors)
Contrast	9,000:1
HDR	HLG / HDR10 supported
Dimming	0-100%
Shaders	No
Refresh rate	3,840 hz
Frame rate	24 / 25 / 29.97 / 30 / 47.95 / 48 / 50 / 59.94 / 60 / 100 / 119.88 / 120 / 144 Hz
Hor. viewing angle	160° +/-5°
Vert. viewing angle	160° +/-5°
Control	Infinipix® Gen2
Communication	tbc
3D	3D Supported
Dimensions (WxLxH)	487.92 x 274.48 cm (192.08 x 108 inches)
Weight / Tile	8.2kg/tile (single PSU) 8.6 kg/tile (dual PSU)
Weight	524.8 kg (single PSU), 550.4 kg (dual PSU)
Operating humidity	10% -80%
Operating temperature	-10°C to +40°C / 14°F to 104°F
IP rating	IP30
Power consumption	775 W/m <sup>2</sup> (max) = total 16,2kW 273 W/m <sup>2</sup> (typ) = total 5,63kW less than 10 W/m <sup>2</sup> (standby) = less than 200W total
BTU per hour	2,404 BTU/h/m <sup>2</sup> (max) 1,026 BTU/h/m <sup>2</sup> (typ)
Power requirements	110-130V/200-240V, 50-60 Hz
Installation	Self-leveling with surface tolerance compensation
Serviceability	Full front & full back service
Module replacement	Automated parallel motorized extraction
Module placement	Guided module placement
Ergonomics	SteadyView driver algorithm to reduce eye fatigu
Certifications	E, UL, FCC class A, RoHS, WEEE, REACH, CCC, RCM
Warranty	3 years, can be extended up to 8 years

**Last updated: 24 May 2024**

© 2018 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check [www.barco.com](http://www.barco.com) for the latest specifications.