

TransForm NDN-210 Pro

Networked Display Node



Barco's TransForm N Networked Display Node is a powerful PC-based networked graphics processor. It is used in the networked visualization environment of a TransForm N system and can display encoded streams coming from the Gbit Ethernet/IP network. H-264, MPEG-4, MPEG-2, MJPEG, V2D and ProServer represent just the top of a long list of supported codecs and streaming formats. Furthermore, the display controller also has a high-end graphics card to perform the rendering operations as are requested by the TransForm N management clients in the network.

High density content – Large display walls

The NDN-210 Pro Output nodes can display high density content and can drive up to sixteen HD displays with a single node. The unit supports multiple different types of displays including the whole range of Barco display solutions like RPC, LCD & LED. Managed by CMS inside the TransForm N system multiple NDN-210 Pro output nodes can be combined in a wall-cluster to show a composed synchronized picture on display walls of virtually unlimited size. The NDN-210 Pro offers a dedicated sync-cable based full frame-lock synchronization between up to 30 nodes suiting the needs of video-walls with advanced synchronization requirements.

Features:

- 4 DisplayPort 1.2 outputs
- Up to 4K-UHD resolution per output
- Universal IP video streaming decoding

- Most extensive list of supported codecs and formats
- Dedicated cable enabled frame lock between multiple display nodes supporting the possibility to cluster up to 30 display nodes together driving a single wall fully synchronized
- Redundant network interface
- Silent operation in a compact and flexible form factor
- Mature Barco quality, robust and reliable

Product specificaties**TRANSFORM NDN-210 PRO****General specifications**

| | |
|-------------------|--|
| Geheugen | 4 GB |
| Harde schijf | 128 GB Solid-State Disk SSD |
| Netwerk | 2x 1Gb/s LAN |
| Grafische kaart | Professional high-performance NVIDIA Quadro-series graphic card |
| Processor | Intel(R) Core(TM) i7 Quad core processor 3.2GHz (4.0GHz max. Turbo frequency) |
| Uitgang | 4x Display Port 1.2 (supporting up to 4x 4K-UHD) 4x DVI-SL via included adapters (supporting up to 4x HD) |
| Invoer | H.264, MPEG-2/4, MxPEG, MJPEG, V2D, H.263, VNC, Pro-Server (see supported codec list) |
| Vormgeving | 3U ½ 19" Rackmount housing |
| Afmetingen | 133mm x 220mm x 300mm 5.24in x 8.66in x 11.81in |
| Voeding | 100-240V, 5-3A, 50/60Hz |
| Energieverbruik | Typ. 124W max. 270W |
| Temperatuurbereik | 0° -40°C 32° -104°F |
| Vochtigheid | Max. 80% (noncondensing) |
| Geluidsniveau | Max. 36dba (measured at 1m/32.8ft distance at 22°/72) |
| Naleving | CE, CB, IEC 609501, ETL, FCC Class A Regulatory Model Id: NGP-210 |
| Bestelgegevens | R9821000B NDN-210 PRO Display Node (US) R9821000F NDN-210 PRO Display Node (EU) R9821000G NDN-210 PRO Display Node (UK) R9821000X NDN-210 PRO Display Node (C13/C14) R9821099 Rackmount Kit for 2x NGP-210 R766042 Pedestal mount kit for NGP-210 |

Laatst bijgewerkt: 08 Jul 2024

© 2024 Barco nv. Alle rechten voorbehouden. Gehele of gedeeltelijke reproductie zonder schriftelijke toestemming is verboden. Alle merknamen en productnamen zijn handelsmerken, geregistreerde handelsmerken of handelsnamen van hun respectieve houders. Als gevolg van voortdurende innovatie kunnen informatie en technische specificaties zonder voorafgaande kennisgeving worden gewijzigd. Controleer www.barco.com voor de nieuwste specificaties.