

MXRT-1451

2D PCIe x1 small form factor display controller



The MXRT-1451 is a low-profile and small form factor PCIe display controller used to drive HIS, RIS and patient list monitors up to 1920 x 1200 display resolution. Since it's a PCIe x1 card, it fits in workstations where all PCIe x16 slots are occupied.

The MXRT-1451 features 1 GB DDR3 display memory, and is compatible with the Windows 8.1 Secure Boot feature.

- Low-profile PCIe x1 MXRT display controller
- 1 GB DDR3 display memory
- Single-wide / low power consumption
- Windows 8.1 SecureBoot compatible

Product specifications**MXRT-1451**

General specifications	
Bus compatibility	PCIe Gen2.1 x1
Power consumption	17 W
Form factor	169.67mm (L) x 64.46mm (H) single PCIe slot wide
Operating system	Windows 7 -32/64-bit, Windows 8.1 -32/64-bit
Platforms	Intel® and AMD architectures
Graphics accelerator	ATI FirePro TM
Display memory	1 GB DDR3
Memory interface	64-bit
Memory bandwidth	9.6 GB/s
Pixel depth	32-bit pixels
Electrical standard	Single-Link DVI complying to v1.0 Display Port (DP) complying to v1.1a
Direct3D hardware support	Microsoft® DirectX v11.0, Vertex Shader 5.0, Pixel Shader 5.0
OpenGL hardware support	OpenGL 4.1
Connectors	DMS-59 to Single-Link DVI
Supported resolutions	Up to 2MP at full refresh rate (VGA at boot-up)
Approvals and compliance	FCC Part 15 Class B, CE EN 55022: 2010 Limit B, EN 55024: 2010, UL-60950-1 2nd Edition 2007-03-27, BMSI CNS 13438 Class B, CISPR-22: 2008-9, CISPR-24: 2010, IEC 60950-1 2005 + A1:2009, VCCI, CSA C22.2, EU RoHS directive (2011/65/EC), Certificate of Information & Communication Equipment (Republic of Korea)
Operating temperature	0° to 60°C (32° to 140° F)
Connectivity	DMS-59 to Single-link DVI-I (1-adaptor is included)

Last updated: 15 Mar 2023

© 2018 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.