

Galaxy 6 Classic+

Stereo dedicated "classic" projector with 1500:1 contrast ratio



技术规格

GALAXY 6 CLASSIC+

一般规格

| 光输出 | 6000 ANSI lumens | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---------------------------|--|-------------|-----------|-------------|---------------------------|--|--|-----------------|---------|------|-------------|---------|-----|--------------------------|--|--|---------------------|---------|------------|---------------------|---------|------------|---------------------|---------|------------|---------------------|---------|------------|
| 分辨率 | 1400 x 1050 (SXGA+) native resolution | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 亮度均匀性 | >90% for the total screen area | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 对比度 | 1500:1 (full white/full black) | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 灯泡 | 1.2 kW (Xenon illumination system) typical lifetime: 1200 hours Max. lifetime: 1500 hours | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 数字微镜器件 | 3 high-resolution SXGA+ active stereo DMD™s | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 特性 | Standard: <ul style="list-style-type: none">· Bi-cubic WARP™· Synchronous and asynchronous active stereo display· DynaColor™/Linked DynaColor™· CLO (Constant Light Output)/ Linked CLO· Stereo-Creator· i-Blend™ (two-or three channel)· economy mode· Shutter Optional: <ul style="list-style-type: none">· Optical Soft Edge Matching (OSEM)· Mono mode· Infitec™ (Switchable)· External polarization (linear or circular)· GISCU™: multi-system and multi-site color management | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 噪音级别 | < 60 dBA at 40°C < 54 dBA at 20°C | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 兼容性 | <ul style="list-style-type: none">· Active stereo capabilities up to SXGA+ at 110Hz· WARP 6™ based pixel map processor using bi-cubic interpolation algorithms for advanced geometry corrections up to a pixelclock of 205 MHz· All current available video sources in RGB or DVI | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 输入 | 1 multifunctional 5-cable input (high bandwidth) for connection of: <ul style="list-style-type: none">· RGB analog signals with standard sync (BNC connectors), sync on green or separate sync· 1 Stereo sync input (mini DIN)· 2 stereo outputs (coax)· 1 DVI input | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 通信 | <ul style="list-style-type: none">· RS232 or RS422 loop-through input (D9-connector) for PC-based projector control· Communication input (D9 connector) for peripherals | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 镜头 | <table><thead><tr><th>Lens type</th><th>order nr.</th><th>throw ratio</th></tr></thead><tbody><tr><td colspan="3">Fixed lens (Manual focus)</td></tr><tr><td>TLD (0.8:1) HB*</td><td>9842040</td><td>0.75</td></tr><tr><td>TLD (1.2:1)</td><td>9840770</td><td>1.1</td></tr><tr><td colspan="3">Motorized zoom and focus</td></tr><tr><td>TLD (1.6-2.0:1) HB*</td><td>9842060</td><td>1.5 to 1.8</td></tr><tr><td>TLD (2.0-2.8:1) HB*</td><td>9842080</td><td>1.8 to 2.6</td></tr><tr><td>TLD (2.8-5.0:1) HB*</td><td>9842100</td><td>2.6 to 4.6</td></tr><tr><td>TLD (5.0-8.0:1) HB*</td><td>9842120</td><td>4.6 to 7.3</td></tr></tbody></table> <p>* High brightness lens</p> | Lens type | order nr. | throw ratio | Fixed lens (Manual focus) | | | TLD (0.8:1) HB* | 9842040 | 0.75 | TLD (1.2:1) | 9840770 | 1.1 | Motorized zoom and focus | | | TLD (1.6-2.0:1) HB* | 9842060 | 1.5 to 1.8 | TLD (2.0-2.8:1) HB* | 9842080 | 1.8 to 2.6 | TLD (2.8-5.0:1) HB* | 9842100 | 2.6 to 4.6 | TLD (5.0-8.0:1) HB* | 9842120 | 4.6 to 7.3 |
| Lens type | order nr. | throw ratio | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Fixed lens (Manual focus) | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| TLD (0.8:1) HB* | 9842040 | 0.75 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| TLD (1.2:1) | 9840770 | 1.1 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Motorized zoom and focus | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| TLD (1.6-2.0:1) HB* | 9842060 | 1.5 to 1.8 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| TLD (2.0-2.8:1) HB* | 9842080 | 1.8 to 2.6 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| TLD (2.8-5.0:1) HB* | 9842100 | 2.6 to 4.6 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| TLD (5.0-8.0:1) HB* | 9842120 | 4.6 to 7.3 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 镜头移动 | Motorized V shift: up to 100% Motorized H shift: up to 65% | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 功率消耗 | 1700 Watts | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 电源 | 230V (tolerance 180V -255V) | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 环境温度 | Max. 35°C | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 净重 | net weight: 124 lbs/56 kg shipping weight: 210 lbs/95 kg | | | | | | | | | | | | | | | | | | | | | | | | | | | |

生成于: 09 Jul 2024

© 2024 巴可公司。保留所有权利。未经书面许可，禁止全部或部分复制。所有品牌名称和产品名称均为其各自持有者的商标、注册商标或商号。由于不断创新，信息和技术规格如有变更，恕不另行通知。请查看www.barco.com.cn以了解最新规格。