

Nio Gray 5.8MP (MDNG-6221) CN

5.8MP high-bright grayscale display



- **Designed for radiology and 2D/3D mammography**
- **High-bright, adjustable tint grayscale**
- **I-Guard and QAWeb Enterprise for always-on compliance**

Are you a radiologist specializing in reading breast cases in mainly grayscale modalities, such as 2D mammography and 3D tomosynthesis? If the answer is yes, then the Nio Gray 5.8MP is cut out just for you. It's fully up to date with capabilities and innovations for today's breast imaging, making this a modern display system that is efficient and easy for you to use. Furthermore, it's also perfectly suited for reading grayscale general radiology images in a comfortably high resolution.

Bigger image, more details

Why 5.8MP? Well, in contrast to conventional 5.2MP display systems, you get 12% more pixels on your screen, which means that you can see more details at any given moment. Combine this with the tall 4:3 aspect ratio, which offers more room to view images in their entirety, and you get an ideal combo to start cutting back on additional panning and zooming.

Reliable reading

The Nio Gray 5.8MP offers you more Just Noticeable Differences, thanks to its high brightness and contrast ratio. Our integrated stability, calibration and uniformity technologies make sure that image quality, light output and DICOM compliance remain consistent over the years.

Efficient workflow

The Nio Gray 5.8MP is more than a grayscale monitor alone. It offers many ways to personalize settings to your liking, such as preferred tints of white or viewing angle. On top of that, it can help you improve your efficiency and speed, thanks to the set of Intuitive Workflow Tools included with our MXRT medical display controllers.

Did you know that SpotView, for example, makes it possible to make an area you choose twice as bright as it was originally? It's been proven to help radiologists



reduce their reading time by as much as 15.5%. You can also define user profiles, saving you and your colleagues time. These automatically adjust the display in situations where it is shared by multiple people.

Long lifetime, clear view

The Nio Gray 5.8MP adheres to the latest medical standards for medical devices in Europe & MQSA in the United States. It's also easy to install our free and highly secured QAWeb Enterprise application, with which you can rely on intervention-free, remote quality assurance. The tool makes it easy for PACS managers to centrally manage their Barco displays' uptime and compliance – anytime, anywhere.

To summarize, your Nio Gray 5.8MP monitor is a functional, easy-to-use diagnostic display system, fully up to date with today's innovations in general grayscale radiology, as well as 2D and 3D mammography. It comes with a 5-year warranty on its all components.

- More detail on your screen, with 5.8MP resolution
- Designed to show breast images entirely, with 3:4 aspect ratio
- Increased contrast, with 1400:1 contrast ratio and 600 to 1000 cd/m² calibrated luminance
- Consistent brightness and grays, with Uniform Luminance Technology and SteadyGray
- Always stable DICOM images and auto QA, with I-Guard front sensor and optionally, QAWeb Enterprise
- Possibility to boost luminance, with I-Luminate and SpotView
- Optional settings and tools to adjust the monitor to your workflow, with Intuitive Workflow Tools

Product specificaties**NIO GRAY 5.8MP (MDNG-6221) CN**

General specifications	
Schermt technologie	LCD
Actief schermformaat (diagonaal)	541 mm (21.3")
Formaat actief scherm (H x V)	324 x 433 mm (12.77" x 17")
Beeldverhouding (H:V)	3:4 for each display in portrait mode, 3:2 overall
Resolutie	5.8 MP (2100 x 2800 pixels)
Pixelpitch	0.1545 mm
Grijsbeeldvorming	Yes
Bit depth	10 bit
Kijkhoek (H, V)	178°
Optical glass	MDNG-6221 option SPEF: Yes MDNG-6221 option SNEF: No
Uniformity correction	ULT
I-Luminate	Yes
SteadyGray	Yes
Voorgeprogrammeerde instellingen voor omgevingslicht	Yes, reading room selection
Ambient light sensor	MDNG-6221 option SPEF: Yes MDNG-6221 option SNEF: No
Voorsensor	Yes
Maximale luminantie	1300 cd/m ²
DICOM-gekalibreerde luminescentie	Warrantied maximum: 1000 cd/m ² Factory default: 600 cd/m ²
Contrastverhouding (paneel standaard)	1400:1
Reactietijd ((stijgtijd + valtijd)/2) (standaard)	12.5 ms
Kleur behuizing	RAL 9003 / RAL 9004
Video-ingangssignalen	DVI-D Dual Link (2x) DisplayPort (2x)
USB-poorten	1x USB 2.0 upstream (endpoint) 2x USB 2.0 downstream
Power rating	24 VDC, 5 A; 5 VDC, 0.1 A
Voedingsvereisten	This device shall only be powered by the following medical approved power supplies: Adapter Technology, type CMD160-P240 Ratings marked on the medical power supply: ■ Input rating: 100–240 VAC, 1.9–0.8 A, 50/60 Hz ■ Output rating: 24 VDC, 6.3 A; 5 VDC, 0.5 A
Energieverbruik	60 W (nominal) < 0.5 W (standby)
Afmetingen met standaard (B x H x D)	Portrait: 378 x 528~628 x 235 mm Landscape: 491 x 472~572 x 235 mm
Afmetingen zonder standaard (B x H x D)	Portrait: 378 x 491 x 81 mm Landscape: 491 x 378 x 81 mm
Afmetingen verpakt (B x H x D)	500 x 280 x 670 mm
Nettogewicht met standaard	MDNG-6221 option SPEF: 11.6 kg MDNG-6221 option SNEF: 10.2 kg

Product specificaties**NIO GRAY 5.8MP (MDNG-6221) CN**

Nettogewicht zonder standaard	MDNG-6221 option SPEF: 6.6 kg MDNG-6221 option SNEF: 5.2 kg
Nettogewicht verpakt	MDNG-6221 option SPEF: 17.0 kg (without optional accessories) MDNG-6221 option SNEF: 15.7 kg (without optional accessories)
Kanteling	-10° to +30°
Zwenking	-45° to +45°
Roteren	90°
Hoogteregelbereik	100 mm
Montagestandaard	VESA (100 mm)
Bescherming van het scherm	MDNG-6221 option SPEF: Protective, anti-reflective glass cover MDNG-6221 option SNEF: N/A
Aanbevolen procedures	All digital images, including digital mammography and breast tomosynthesis
Certificeringen	CCC (China) Safety specific: GB 4943.1-2011 EMI specific: GB 17625.1-2012 GB/T9254.1-2021 Environmental: China Energy Label, CECP, China RoHS, WEEE
Meegeleverde accessoires	User guide System sheet Video cable (1 x DisplayPort) Mains cable(s) USB 2.0 cable External power supply
Software voor kwaliteitsgarantie	QAWeb
Garantie	5 years, including 40000 hrs backlight warranty
Bedrijfstemperatuur	0 °C to 40 °C (15 °C to 30 °C within specs)
Opslagtemperatuur	-20 °C to 60 °C
Vochtigheid in bedrijf	8% to 80% (non-condensing)
Vochtigheid bij opslag	5% to 85% (non-condensing)
Bedrijfsdruk	70 kPa minimum
Opslagdruk	50 to 106 kPa

Laatst bijgewerkt: 18 Mar 2024

© 2018 Barco nv. Alle rechten voorbehouden. Gehele of gedeeltelijke reproductie zonder schriftelijke toestemming is verboden. Alle merknamen en productnamen zijn handelsmerken, geregistreerde handelsmerken of handelsnamen van hun respectieve houders. Vanwege voortdurende innovatie kunnen informatie en technische specificaties zonder voorafgaande kennisgeving worden gewijzigd. Raadpleeg www.barco.com voor de meest recente specificaties.