

# Magik II

Universal VGA interface



## Product specifications

## MAGIK II

### General specifications

Inputs	<ul style="list-style-type: none"><li>• RGB analog on 5 BNC</li><li>• Signal levels: R, G, B: 0.7 Vpp (no sync) or 1 Vpp with sync @ 75 Ohm</li><li>• Sync: TTL @ 22 K load/analog</li></ul>
Outputs	<ul style="list-style-type: none"><li>• RGB analog on 5 BNC connectors (to projector or monitor): R, G, B: 0.7 Vpp (no sync) or 1 Vpp with sync @ 75 Ohm</li><li>• RGB analog loop through on D15 connector (local monitor out): R, G, B: 0.7 Vpp (no sync) or 1 Vpp with sync 75 Ohm</li><li>• Gain fixed to 1</li><li>• Two LEDs indicate signal presence on the BNC sync output (H)</li></ul>
RGB Bandwidth	300 MHz @ -3dB
Compatibility	All desktop or portable computers with resolutions from VGA up to QXGA (2,048 x 1,532)
Standard accessories	Included: <ul style="list-style-type: none"><li>• Bracket and set of wing screws for easy mounting underneath a table or any other enclosure</li><li>• Two power cords for both US and European power outlets</li></ul>
AC power	Auto ranging power supply 87 -240 V AC 50/60 Hz
Safety Regulations	Compliant with UL1950 and EN60950
Electromagnetic Interference	Barco's Magik II complies with FCC rules & regulations, part 15 Class B and CE EN55022 Class B
Dimensions	width x height x depth 218 x 45 x 150 mm 5.58 x 1.77 x 6.30 inch
Weight	1.20 kg / 2.64 lbs.
Optional	19" rack mount (order n° R9828970)

Last updated: 09 Jul 2024

© 2024 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check [www.barco.com](http://www.barco.com) for the latest specifications.