

# iQ Pro G300



## 技术规格

## IQ PRO G300

### 一般规格

光输出	3,500 ANSI lumen
亮度均匀性	>95 % for the total screen
对比度	>400: 1 (full white/full black)
液晶面板	3 active matrix 1.3" diagonal XGA polysilicon LCD panels with Micro Lens Arrays and a resolution of 1024 x 768 pixels (aspect ratio 4:3).
分辨率	1024 x 768 (native)
网络	iQ Pro Server Specifications: -Processing Power: Pentium III socket with 1,2 Gigahertz Tualatin Celeron processor -Memory: 256 MB RAM -Storage: 40 GB hard disk -Video memory up to 64 MB -Inputs and outputs <ul style="list-style-type: none"><li>▪ PCMCIA slot for Wireless LAN cards, memory cards, Bluetooth, input extensions ...</li><li>▪ RJ45 connector for Ethernet (10Mb/s) and Fast Ethernet (100Mb/s)</li><li>▪ 4 USB connectors</li><li>▪ Audio: 3.5 mm jacks for Microphone in, Line in and Line out</li></ul>
特性	<ul style="list-style-type: none"><li>▪ Advanced picture-in-picture</li><li>▪ Seamless switching with effects</li><li>▪ Standard cable basket</li><li>▪ Standard light shutter</li><li>▪ Advanced digital zoom</li></ul>
兼容性	The iQ Pro G300 is compatible with: <ul style="list-style-type: none"><li>▪ All current video sources (PAL, SECAM, NTSC) in Composite, S-VHS, Component or RGB formats</li><li>▪ All currently proposed HDTV, extended and improved television standards (1080i, 720p)</li><li>▪ All computer graphics formats from VGA, SVGA, XGA, SXGA to UXGA</li><li>▪ Most Macintosh computers</li><li>▪ Electronic workstations with a resolution up to 1600 x 1200 pixels at 75 Hz</li><li>▪ Most computer sources with a pixel clock up to 160 MHz</li><li>▪ DVI sources up to SXGA</li></ul>
屏幕尺寸	From 1-6 m/3-20 ft.
输入	1x Configurable 5-Wire (BNC) for: Composite Video, S-Video, Component Video, RGBHV, RGBS, RGsB. 1x Composite Video (BNC) (up to 7 Composite Video's when using all connectors on top input board) 1x S-Video (4-pin mini-DIN) (up to 3 S-Video's when combining BNC's) 1x VGA (D15 connector) 1x DVI (Digital Visual Interface)
灯泡	2x 200 Watt UHP lamp, in lamp housing Typical lifetime: 1500 h/lamp. 1500 hours in Dual Lamp Mode or max. 3000 hours/set in Single Lamp Mode.
镜头	Fixed focal length lenses are available with a throw ratio of 0.85:1 (very short throw ratio, specially designed for rear screen on-axis projection) or 7.0:1 (long throw).  Variable focus lenses with a throw distance of 1.3-1.8, 1.9-2.6, 3.0-6.0 times the screen width
扫描频率	Horizontal 15 kHz -110 kHz Vertical 25 Hz -150 Hz
镜头移动	QVD Lenses Motorized V shift: -30% +120%  For specific details per lens type: see lens product pages
尺寸(宽x长x高)	Projector body with cable basket: 415 mm (Max W) x 195 mm (Max H) x 565 mm (Max D) Projector body without cable basket: 415 mm (Max W) x 195 mm (Max H) x 487 mm (Max D)
净重	Net weight, body only: 12.9kg/28.5 lbs.
通信	1x D9 connectors for RS232 In/Out 1x spherical IR receiver
噪音级别	
电源	Power factor pre-regulated SMPS, 90-254 VAC / 50-60Hz
功率消耗	Max 550 Watt
功率消耗	Max 1878 BTU/h
安全级别	Compliant with UL1950 and EN60950
电磁干扰	BARCO's iQ Pro G300 complies with FCC rules & regulations, part 15 Class B and CE EN55022 Class B
无缝切换	Standard

生成于: 09 Jul 2024

© 2024 巴可公司。保留所有权利。未经书面许可，禁止全部或部分复制。所有品牌名称和产品名称均为其各自持有者的商标、注册商标或商号。由于不断创新，信息和技术规格如有变更，恕不另行通知。请查看[www.barco.com.cn](http://www.barco.com.cn)以了解最新规格。