

iQ Pro G400



Especificações técnicas

IQ PRO G400

Especificações gerais

Saída de luz	4.200 ANSI lumen
Uniformidade de brilho	>95 % for the total screen
Razão de contraste	>400 : 1 (full white/full black)
Tela de LCD	3 active matrix 1.3" diagonal XGA polysilicon LCD panels with Micro Lens Arrays and a resolution of 1024 x 768 pixels (aspect ratio 4:3).
Resolução	1024 x 768 (native)
Rede	IQ Pro Server Specifications: -Processing Power: Pentium III socket with 1,2 Gigahertz Tualatin Celeron processor -Memory: 256 MB RAM - Storage: 40 GB hard disk -Video memory up to 64 MB -Inputs and outputs <ul style="list-style-type: none">▪ PCMCIA slot for Wireless LAN cards, memory cards, Bluetooth, input extensions ...▪ RJ45connector for Ethernet (10Mb/s) and Fast Ethernet (100Mb/s)▪ 4 USB connectors▪ Audio: 3,5 mm jacks for Microphone in, Line in and Line out
Recursos	-Advanced picture-in-picture - Seamless switching with effects - Standard cable basket - Standard light shutter - Advanced digital zoom
Compatibilidade	The IQ Pro G400 is compatible with: <ul style="list-style-type: none">▪ All current video sources (PAL,SECAM, NTSC) in Composite, S-VHS, Component or RGB formats▪ All currently proposed HDTV, extended and improved television standards (1080i, 720p)▪ All computer graphics formats from VGA, SVGA, XGA, SXGA to UXGA▪ Most Macintosh computers▪ Electronic workstations with a resolution up to 1600 x 1200 pixels at 75 Hz▪ Most computer sources with a pixel clock up to 160 MHz▪ DVI sources up to SXGA
Tamanho da tela	From 1-6 m/3-20 ft.
Entradas	1x Configurable 5-Wire (BNC) for: Composite Video, S-Video, Component Video , RGBHV, RGBS, RGBS. 1x Composite Video (BNC) (up to 7 Composite Video's when using all connectors on top input board) 1x S-Video (4-pin mini-DIN) (up to 3 S-Video's when combining BNC's) 1x VGA (D15 connector) 1x DVI (Digital Visual Interface)
Lâmpada	2x 250 Watt UHP lamp, in lamp housing Typical lifetime: 1000 h/lamp. 1000 hours in Dual Lamp Mode or max. 2000 hours/set in Single Lamp Mode.
Lentes	Fixed focal length lenses are available with a throw ratio of 0.85:1 (very short throw ratio, specially designed for rear screen on-axis projection) or 7.0:1 (long throw). Variable focus lenses with a throw distance of 1.3-1.8,1.9-2.6, 3.0-6.0 times the screen width
Frequências de Varredura	Horizontal 15 kHz -110 kHz Vertical 25 Hz -150 Hz
Deslocamento de Lente	QVD Lenses Motorized V shift: -30% +120% For specific details per lens type: see lens product pages
Dimensões (LxPxA)	Projector body with cable basket: 415 mm (Max W) x 195 mm (Max H) x 565 mm (Max D) Projector body without cable basket: 415 mm (Max W) x 195 mm (Max H) x 487 mm (Max D)
Peso	Net weight, body only: 12.9kg/28.5 lbs.
Comunicação	1x D9 connectors for RS232 In/Out 1x spherical IR receiver
Nível de Ruído	
Energia de CA	Power factor pre-regulated SMPS, 90-254 VAC / 50-60Hz
Consumo de energia	Max 650 Watt
Dissipação de Potência	Max 2219 BTU/h
Comutação sem emendas	Standard

Gerada em: 09 Jul 2024

© 2024 Barco nv. Todos os direitos reservados. A reprodução total ou parcial sem permissão por escrito é proibida. Todos os nomes de marca e produto são marcas comerciais, marcas comerciais registradas ou nomes dos respectivos proprietários. Por causa da inovação contínua, as informações e as especificações técnicas estão sujeitas a alterações sem aviso prévio. Verifique www.barco.com para obter as especificações mais recentes.